

屋内照明器具特性

品番(品名)	NND2 6 2 2 0 Z	
光源	NND2 6 2 2 0 Z (ALL) × 1 6 0 0 . 0 1 m	
管理番号	K 0 1 2 8 7 2 4 (3) D B 1	
B Z 分類	B Z 1	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %		
下方光束	100 %		床	10 %				10 %				10 %				10 %				0 %	
		室指数	照明率 (× 0 . 0 1)																Z C M		
保守率	良	0.45	0.6	99	97	95	94	99	96	95	94	98	96	95	94	97	96	94	94	93	
	中		0.8	101	99	97	96	101	99	97	96	100	98	97	96	99	98	96	96	95	
	否		1.0	103	100	99	98	102	100	99	98	101	99	98	97	100	99	98	97	96	
			1.25	104	102	100	99	103	101	100	99	102	100	99	98	101	100	99	98	97	
下方投影面積	cm ²	等価発光面積	cm ²	1.5	104	103	101	100	104	102	101	100	102	101	100	99	101	100	99	97	
				2.0	105	104	103	102	105	103	102	101	103	102	101	101	102	101	100	100	98
取付高さ	器具間隔最大限		H _m	0.29 H _m	0.28 H _m	2.5	106	105	104	103	105	104	103	102	104	103	102	101	101	100	99
	横方向 (A)	縦方向 (B)				3.0	106	105	105	104	106	105	104	103	104	103	102	102	102	101	101
						4.0	107	106	105	105	106	105	105	104	104	104	103	103	102	101	99
						5.0	107	107	106	106	106	106	105	105	104	104	103	103	102	102	100
						7.0	108	107	107	106	107	106	106	106	105	104	104	103	103	102	100
						10.0	108	108	107	107	107	107	106	106	105	105	104	103	103	103	100

