

屋内照明器具特性

品番 (品名)	LSR12-4-29 (XLX430BSNT)	
光源	LED5000_85_2900 x1 2900.0 lm	
管理番号	K0140212 (3) DR1	
BZ分類	BZ6	

器具効率	100%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	14%	床	10%				10%				10%				10%				0%			
下方光束	86%	室指数	照明率 (X0.01) ZCM																			
保守率	良 0.81 中 0.77 否 0.68	0.6	52	39	31	25	50	38	30	25	46	36	29	24	42	34	28	23	20			
		0.8	61	49	41	35	59	48	40	34	54	45	38	33	50	42	36	32	28			
		1.0	68	56	48	42	65	55	47	41	60	51	45	39	56	48	42	38	34			
		1.25	74	63	55	49	71	61	54	48	66	57	51	46	61	54	49	44	40			
下方投影面積	cm ²	1.5	78	68	60	54	75	66	59	53	69	62	56	51	64	58	53	49	44			
		2.0	83	75	68	62	80	73	66	61	75	68	63	58	70	64	60	56	51			
取付高さ	器具間隔最大限		2.5	87	80	73	68	84	77	72	67	78	73	68	64	73	68	64	61	55		
	横方向 (A)	縦方向 (B)	3.0	90	83	77	72	87	81	75	71	81	76	72	68	76	72	68	65	59		
1.5m	1.59m	2.11m	4.0	93	88	83	79	90	85	81	77	84	80	77	73	79	76	73	70	64		
2	2.11	2.66	5.0	95	91	86	83	92	88	84	81	86	83	80	77	81	78	76	73	67		
2.5	2.63	3.23	7.0	98	94	91	88	95	91	88	86	89	86	84	82	84	82	80	78	71		
3	3.15	3.82	10.0	100	97	94	92	97	94	92	90	91	89	87	85	86	84	83	81	75		

