

屋内照明器具特性

品番 (品名)	NNF 4 1 2 3 1 C														
光源	LDL40S.N/19/25-K ×1 2500.0 lm														
管理番号	K0126632(4)DB1														
BZ分類	BZ6														

器具効率	89 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %			
上方光束	19 %	室指数	照明率 (X0.01)																ZCM	
下方光束	70 %																			
保守率	良 中 否	0.81	0.6	45	34	27	22	43	33	26	21	39	30	25	20	35	28	23	19	16
		0.77	0.8	53	42	35	29	50	40	34	29	46	37	31	27	41	35	29	25	22
			1.0	58	48	40	35	55	46	39	34	50	42	36	32	46	39	34	30	26
		0.68	1.25	63	53	46	40	60	51	45	39	55	47	42	37	50	44	39	35	30
下方投影面積	c m ²	1.5	67	58	51	45	64	55	49	44	58	51	46	41	52	47	42	39	33	
		2.0	72	64	57	52	68	61	55	50	62	56	52	47	57	52	48	44	39	
取付高さ	器具間隔最大限		2.5	75	68	62	57	72	65	60	55	65	60	56	52	60	55	52	48	42
	横方向 (A)	縦方向 (B)	3.0	77	71	66	61	74	68	63	59	68	63	59	55	62	58	55	52	45
1.5m	1.63 m	2.11 m	4.0	80	75	70	66	77	72	68	64	71	67	63	60	65	62	59	56	49
2	2.15	2.65	5.0	82	78	74	70	79	75	71	68	73	69	66	63	67	64	62	59	52
2.5	2.67	3.22	7.0	84	81	78	75	81	78	75	72	75	72	70	68	69	67	65	63	56
3	3.19	3.79	10.0	86	84	81	79	83	81	78	76	77	75	73	71	71	70	68	67	59

