

屋内照明器具特性	
品番 (品名)	NNF 4 1 8 7 2
光源	LDL40S.N/29/38(3800B) ×1 3800.0 1m
管理番号	K0132948(0)DR1
BZ分類	BZ5/8.5/BZ6

器具効率	70%	天井	80%				70%				50%				30%				0%	
	上方光束 69%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	1%	床		10%				10%				10%				10%				0%
室指数			照明率 (X0.01)																ZCM	
保守率	良 0.86	0.6	30	23	18	15	26	20	16	13	17	14	11	9	10	8	7	6	0	
	中 0.81	0.8	35	28	24	20	30	25	21	18	21	17	14	13	12	10	9	8	0	
	否 0.76	1.0	39	33	28	25	34	28	24	21	23	20	17	15	13	12	10	9	0	
		1.25	43	37	32	29	37	32	28	25	25	22	20	18	15	13	12	11	0	
下方投影面積	cm ²	1.5	45	40	36	32	39	34	31	28	27	24	22	20	16	14	13	12	0	
等価発光面積	cm ²	2.0	49	44	41	37	42	38	35	33	29	27	25	23	17	16	15	14	0	
取付高さ	器具間隔最大限		2.5	51	47	44	41	44	41	38	36	30	28	27	25	18	17	16	15	0
	横方向 (A)	縦方向 (B)	3.0	52	49	46	44	45	42	40	38	31	30	28	27	18	18	17	16	0
1.5m	2.08m	2.15m	4.0	54	52	49	47	47	45	43	41	33	31	30	29	19	19	18	17	0
2	2.72	2.67	5.0	55	53	51	49	48	46	44	43	33	32	31	30	20	19	19	18	1
2.5	3.37	3.28	7.0	57	55	54	52	49	48	47	45	34	34	33	32	20	20	19	19	1
3	4	3.94	10.0	58	57	56	54	50	49	48	47	35	34	34	33	21	20	20	20	1

