

屋内照明器具特性	
品番 (品名)	NNF 4 2 0 4 0 J
光源	LDL40S . N / 29 / 38 (3800A) × 2 3800 . 0 1 m
管理番号	K0126622 (1) DB 1
B Z 分類	BZ6

器具効率	98 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	14 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	84 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.93 0.9 0.86	0.6	50	38	30	24	48	37	29	24	45	35	28	23	41	33	27	22	19	
		0.8	59	47	39	33	57	46	38	33	53	43	37	31	49	41	35	30	27	
		1.0	66	54	46	40	63	52	45	39	58	49	43	37	54	46	41	36	32	
		1.25	71	61	53	46	68	59	51	46	63	55	49	44	59	52	46	42	38	
下方投影面積	c m ²	1.5	75	65	58	52	72	63	56	51	67	60	54	49	62	56	51	46	42	
		2.0	81	72	65	60	78	70	64	58	72	66	61	56	67	62	57	53	48	
取付高さ	器具間隔最大限		2.5	84	77	71	65	81	75	69	64	76	70	65	61	71	66	62	58	53
	横方向 (A)	縦方向 (B)	3.0	87	80	75	70	84	78	73	68	78	73	69	65	73	69	65	62	57
1.5m	2.17 m	2.12 m	4.0	90	85	80	76	87	82	78	74	82	78	74	71	77	73	70	67	61
2	2.86	2.68	5.0	92	88	84	80	90	85	82	78	84	81	77	74	79	76	73	71	65
2.5	3.56	3.26	7.0	95	91	88	85	92	89	86	83	87	84	81	79	81	79	77	75	69
3	4.24	3.84	10.0	97	94	92	89	94	92	89	87	89	87	85	83	84	82	80	79	73

