

屋内照明器具特性

品番 (品名)	NNF 4 2 0 4 0 J										
光源	LDL40S . N / 23 / 24 (2400) ×2 2400 . 0 1 m										
管理番号	K0127329 (1) DB 1										
B Z 分類	B Z 6										

器具効率	98 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	15 %	室指数																	照明率 (X0.01)																	Z C M																
下方光束	83 %																																																			
保守率	良 中 否	0.83	0.6	50	37	29	24	48	36	29	23	44	34	27	23	40	32	26	22	19																																
		0.81	0.8	59	47	39	33	57	45	38	32	52	43	36	31	48	40	34	29	26																																
			1.0	65	54	45	39	63	52	44	38	58	49	42	37	53	45	40	35	31																																
		0.77	1.25	71	60	52	46	68	58	51	45	63	54	48	43	58	51	45	41	37																																
下方投影面積	c m ²	1.5	75	65	57	51	72	63	56	50	66	59	53	48	61	55	50	46	41																																	
		2.0	81	72	65	59	77	70	63	58	72	65	60	55	66	61	56	52	47																																	
取付高さ	器具間隔最大限		2.5	84	77	70	65	81	74	68	63	75	70	65	60	70	65	61	57	52																																
	横方向 (A)	縦方向 (B)	3.0	87	80	74	69	84	78	72	68	78	73	68	64	72	68	65	61	55																																
1.5 m	2.19 m	2.16 m	4.0	90	85	80	75	87	82	78	74	81	77	73	70	76	72	69	66	60																																
2	2.89	2.74	5.0	92	88	83	80	89	85	81	78	84	80	77	74	78	75	72	70	64																																
2.5	3.59	3.33	7.0	95	91	88	85	92	89	86	83	86	83	81	78	81	79	76	74	68																																
3	4.28	3.92	10.0	97	94	92	89	94	92	89	87	88	86	84	82	83	81	80	78	72																																

