

屋内照明器具特性

品番 (品名)	NNF J 4 2 8 4 8									
光源	LDL40S . N / 29 / 31 - 9 (3150 A) × 2 3150.0 1 m									
管理番号	K0127197 (3) DB 1									
B Z 分類	BZ6 / 4.5 / BZ5 / 6.0 / BZ6									

器具効率	93 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	5 %																			
下方光束	88 %																			
室指数	照明率 (X0.01)																		ZCM	
保守率	良 中 否	0.93	0.6	49	37	30	24	48	37	29	24	45	35	29	24	42	34	28	23	21
		0.9	0.8	58	47	39	33	56	46	38	33	53	44	37	32	50	42	36	32	29
			1.0	64	53	46	40	62	52	45	39	59	50	43	38	55	48	42	38	35
		0.86	1.25	70	60	52	46	68	58	51	46	64	56	50	45	60	54	48	44	41
下方投影面積	c m ²	1.5	74	64	57	51	72	63	56	51	68	60	54	50	64	58	53	49	45	
		2.0	79	71	65	59	77	70	64	59	73	67	62	57	69	64	60	56	52	
取付高さ	器具間隔最大限		2.5	83	76	70	65	81	74	69	64	76	71	66	62	73	68	64	61	57
	横方向 (A)	縦方向 (B)	3.0	85	79	74	69	83	77	73	68	79	74	70	66	75	71	68	65	61
1.5m	2.14 m	2.11 m	4.0	88	83	79	75	86	82	78	74	82	79	75	72	79	75	73	70	66
2	2.83	2.68	5.0	90	86	82	79	88	85	81	78	85	81	78	76	81	78	76	73	69
2.5	3.52	3.25	7.0	93	90	87	84	91	88	85	83	87	85	82	80	83	81	79	78	73
3	4.19	3.84	10.0	95	92	90	88	93	91	89	87	89	87	86	84	86	84	83	81	77

