

屋内照明器具特性

品番 (品名)	NNF W4 1 8 2 5														
光源	LDL40S.N/14/26(2600A) ×1 2600.0 1 m														
管理番号	K0125169(0)DR1														
BZ分類	BZ7/0.9/BZ6/3.5/BZ7/4.5/BZ6/6.0/BZ7														

器具効率	78%	天井	80%				70%				50%				30%				0%		
	上方光束		39%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		39%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01) ZCM																				
保守率	良	0.77	0.6	3.6	2.7	2.1	1.7	3.3	2.5	2.0	1.6	2.8	2.1	1.7	1.3	2.2	1.7	1.4	1.1	0.7	
	中	0.72	0.8	4.3	3.4	2.8	2.3	3.9	3.1	2.6	2.2	3.3	2.6	2.2	1.9	2.7	2.2	1.8	1.6	1.0	
	否	0.68	1.0	4.8	3.9	3.3	2.8	4.4	3.6	3.0	2.6	3.6	3.0	2.6	2.3	3.0	2.5	2.2	1.9	1.3	
	下方投影面積	c m ²		1.25	5.2	4.4	3.8	3.3	4.8	4.1	3.5	3.1	4.0	3.4	3.0	2.7	3.2	2.8	2.5	2.2	1.5
等価発光面積	c m ²		1.5	5.5	4.8	4.2	3.7	5.1	4.4	3.9	3.5	4.2	3.7	3.3	3.0	3.5	3.1	2.8	2.5	1.7	
	c m ²		2.0	5.9	5.3	4.8	4.3	5.5	4.9	4.4	4.0	4.6	4.1	3.8	3.5	3.8	3.4	3.1	2.9	2.0	
取付高さ	器具間隔最大限		2.5	6.2	5.6	5.2	4.8	5.7	5.2	4.8	4.4	4.8	4.4	4.1	3.8	4.0	3.7	3.4	3.2	2.2	
	横方向 (A)	縦方向 (B)	3.0	6.4	5.9	5.5	5.1	5.9	5.5	5.1	4.7	5.0	4.6	4.3	4.1	4.1	3.9	3.6	3.4	2.4	
1.5m	2.31m	2.14m	4.0	6.6	6.2	5.9	5.5	6.1	5.8	5.5	5.2	5.2	4.9	4.7	4.4	4.3	4.1	3.9	3.7	2.7	
2	3.05	2.68	5.0	6.8	6.5	6.1	5.8	6.3	6.0	5.7	5.5	5.3	5.1	4.9	4.7	4.4	4.3	4.1	3.9	2.8	
2.5	3.79	3.25	7.0	7.0	6.7	6.5	6.2	6.5	6.3	6.0	5.8	5.5	5.3	5.2	5.0	4.6	4.5	4.3	4.2	3.0	
3	4.53	3.83	10.0	7.2	6.9	6.8	6.6	6.6	6.5	6.3	6.1	5.7	5.5	5.4	5.3	4.7	4.6	4.5	4.4	3.2	

