

# 屋内照明器具特性

品番 (品名)	NNLK41109 + NNL4001NN														
光源	LED5000_85_9500 x1 9500.0lm														
管理番号	K0135074 (* ) DB 1														
BZ分類	BZ5														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	4 %	室指数	照明率 ( X0.01 )																ZCM		
下方光束	96 %																				
保守率	良	0.83	0.6	5.6	4.4	3.6	3.0	5.4	4.3	3.6	3.0	5.2	4.2	3.5	3.0	4.9	4.0	3.4	3.0	2.7	
	中	0.81	0.8	6.6	5.4	4.6	4.1	6.4	5.3	4.6	4.0	6.1	5.1	4.5	4.0	5.8	5.0	4.4	3.9	3.7	
	否	0.77	1.0	7.2	6.1	5.4	4.8	7.0	6.0	5.3	4.7	6.7	5.8	5.2	4.7	6.4	5.6	5.1	4.6	4.3	
			1.25	7.8	6.8	6.1	5.5	7.6	6.7	6.0	5.5	7.2	6.5	5.9	5.4	6.9	6.2	5.7	5.3	5.0	
下方投影面積			1.5	8.2	7.3	6.6	6.0	8.0	7.2	6.5	6.0	7.6	6.9	6.4	5.9	7.3	6.7	6.2	5.8	5.5	
	等価発光面積		2.0	8.8	8.0	7.4	6.9	8.6	7.9	7.3	6.8	8.2	7.6	7.1	6.7	7.8	7.3	6.9	6.5	6.2	
取付高さ	器具間隔最大限		2.5	9.1	8.5	7.9	7.4	8.9	8.3	7.8	7.3	8.5	8.0	7.6	7.2	8.2	7.7	7.4	7.0	6.7	
		横方向 (A)	縦方向 (B)	3.0	9.4	8.8	8.3	7.8	9.2	8.6	8.2	7.8	8.8	8.3	7.9	7.6	8.4	8.1	7.7	7.4	7.1
1.5m	1.94m	2.1m	4.0	9.7	9.2	8.8	8.4	9.5	9.0	8.7	8.3	9.1	8.7	8.4	8.1	8.8	8.5	8.2	7.9	7.6	
2	2.56	2.64	5.0	9.9	9.5	9.1	8.8	9.7	9.3	9.0	8.7	9.3	9.0	8.7	8.5	9.0	8.7	8.5	8.3	7.9	
2.5	3.19	3.21	7.0	10.1	9.8	9.5	9.3	9.9	9.6	9.4	9.1	9.6	9.3	9.1	8.9	9.2	9.0	8.8	8.7	8.3	
3	3.8	3.79	10.0	10.3	10.1	9.8	9.6	10.1	9.9	9.7	9.5	9.7	9.6	9.4	9.3	9.4	9.3	9.1	9.0	8.6	

