

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | NNLK41315 + NNL4400ENT       |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_3880 x1 3880.0 lm |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0137984 (* ) DB 1           |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ5/4.5/BZ4/6.0/BZ5/8.5/BZ4  |  |  |  |  |  |  |  |  |  |

|        |         |         |               |      |     |     |      |      |     |     |      |      |    |    |      |      |    |    |     |     |
|--------|---------|---------|---------------|------|-----|-----|------|------|-----|-----|------|------|----|----|------|------|----|----|-----|-----|
| 器具効率   | 100 %   | 天井      | 80 %          |      |     |     | 70 % |      |     |     | 50 % |      |    |    | 30 % |      |    |    | 0 % |     |
|        |         |         | 壁             | 70   | 50  | 30  | 10   | 70   | 50  | 30  | 10   | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10  | 0 % |
| 上方光束   | 0 %     | 反射率     | 10 %          |      |     |     | 10 % |      |     |     | 10 % |      |    |    | 10 % |      |    |    | 0 % |     |
| 下方光束   | 100 %   |         | 床             | 10 % |     |     |      | 10 % |     |     |      | 10 % |    |    |      | 10 % |    |    |     | 0 % |
|        |         | 室指数     | 照明率 ( X0.01 ) |      |     |     |      |      |     |     |      |      |    |    |      |      |    |    | ZCM |     |
| 保守率    | 良       | 0.81    | 0.6           | 57   | 45  | 37  | 31   | 55   | 44  | 36  | 31   | 53   | 43 | 36 | 31   | 51   | 42 | 36 | 31  | 29  |
|        | 中       | 0.77    | 0.8           | 67   | 55  | 48  | 42   | 65   | 55  | 47  | 42   | 63   | 53 | 46 | 41   | 60   | 52 | 46 | 41  | 39  |
|        | 否       | 0.68    | 1.0           | 74   | 63  | 55  | 49   | 72   | 62  | 55  | 49   | 69   | 60 | 54 | 49   | 66   | 59 | 53 | 49  | 46  |
|        |         |         | 1.25          | 80   | 70  | 63  | 57   | 78   | 69  | 62  | 57   | 75   | 67 | 61 | 56   | 72   | 66 | 60 | 56  | 54  |
| 下方投影面積 |         |         | 1.5           | 84   | 75  | 68  | 63   | 82   | 74  | 68  | 63   | 79   | 72 | 67 | 62   | 76   | 70 | 65 | 61  | 59  |
|        |         |         | 2.0           | 90   | 82  | 76  | 71   | 88   | 81  | 76  | 71   | 85   | 79 | 74 | 70   | 82   | 77 | 73 | 69  | 67  |
| 取付高さ   | 器具間隔最大限 |         | 2.5           | 93   | 87  | 82  | 77   | 91   | 86  | 81  | 77   | 88   | 84 | 79 | 76   | 86   | 82 | 78 | 75  | 72  |
|        | 横方向 (A) | 縦方向 (B) | 3.0           | 96   | 90  | 86  | 82   | 94   | 89  | 85  | 81   | 91   | 87 | 83 | 80   | 88   | 85 | 82 | 79  | 76  |
| 1.5m   | 1.95m   | 2.16m   | 4.0           | 99   | 94  | 91  | 87   | 97   | 93  | 90  | 87   | 94   | 91 | 88 | 85   | 92   | 89 | 86 | 84  |     |
| 2      | 2.58    | 2.72    | 5.0           | 101  | 97  | 94  | 91   | 99   | 96  | 93  | 90   | 96   | 94 | 91 | 89   | 94   | 91 | 89 | 87  |     |
| 2.5    | 3.21    | 3.3     | 7.0           | 103  | 100 | 98  | 96   | 101  | 99  | 97  | 95   | 99   | 97 | 95 | 93   | 96   | 95 | 93 | 91  |     |
| 3      | 3.83    | 3.9     | 10.0          | 104  | 103 | 101 | 99   | 103  | 101 | 100 | 98   | 100  | 99 | 98 | 96   | 98   | 97 | 96 | 95  |     |

