

# 屋内照明器具特性

|         |                                   |  |
|---------|-----------------------------------|--|
| 品番 (品名) | NNLK41515J + NNL4601NN            |  |
| 光源      | LED5000_85_6550 x1      6550.0 lm |  |
| 管理番号    | K0128261 (* ) DB 1                |  |
| BZ分類    | BZ5                               |  |

|        |                  |         |               |      |      |     |      |      |      |     |      |     |      |     |      |     |      |     |     |     |     |  |     |
|--------|------------------|---------|---------------|------|------|-----|------|------|------|-----|------|-----|------|-----|------|-----|------|-----|-----|-----|-----|--|-----|
| 器具効率   | 100 %            | 天井      | 80 %          |      |      |     | 70 % |      |      |     | 50 % |     |      |     | 30 % |     |      |     | 0 % |     |     |  |     |
|        |                  |         | 反射率           | 壁    | 70   | 50  | 30   | 10   | 70   | 50  | 30   | 10  | 70   | 50  | 30   | 10  | 70   | 50  | 30  | 10  | 0 % |  |     |
|        |                  |         |               | 床    | 10 % |     |      |      | 10 % |     |      |     | 10 % |     |      |     | 10 % |     |     |     | 0 % |  |     |
| 上方光束   | 4 %              | 室指数     | 照明率 ( X0.01 ) |      |      |     |      |      |      |     |      |     |      |     |      |     |      |     |     |     |     |  | ZCM |
| 下方光束   | 96 %             |         |               |      |      |     |      |      |      |     |      |     |      |     |      |     |      |     |     |     |     |  |     |
| 保守率    | 良<br>中<br>否      | 0.83    | 0.6           | 5.5  | 4.2  | 3.4 | 2.9  | 5.3  | 4.1  | 3.4 | 2.8  | 5.0 | 4.0  | 3.3 | 2.8  | 4.8 | 3.9  | 3.2 | 2.8 | 2.5 |     |  |     |
|        |                  | 0.81    | 0.8           | 6.4  | 5.3  | 4.4 | 3.8  | 6.3  | 5.2  | 4.4 | 3.8  | 5.9 | 5.0  | 4.3 | 3.8  | 5.6 | 4.8  | 4.2 | 3.7 | 3.5 |     |  |     |
|        |                  | 0.77    | 1.0           | 7.1  | 6.0  | 5.2 | 4.6  | 6.9  | 5.9  | 5.1 | 4.5  | 6.5 | 5.6  | 5.0 | 4.5  | 6.2 | 5.4  | 4.9 | 4.4 | 4.1 |     |  |     |
|        |                  |         | 1.25          | 7.7  | 6.7  | 5.9 | 5.3  | 7.5  | 6.5  | 5.8 | 5.2  | 7.1 | 6.3  | 5.7 | 5.2  | 6.8 | 6.1  | 5.5 | 5.1 | 4.8 |     |  |     |
| 下方投影面積 | c m <sup>2</sup> | 1.5     | 8.1           | 7.2  | 6.4  | 5.8 | 7.9  | 7.0  | 6.3  | 5.8 | 7.5  | 6.8 | 6.2  | 5.7 | 7.1  | 6.5 | 6.0  | 5.6 | 5.3 |     |     |  |     |
|        |                  | 2.0     | 8.7           | 7.9  | 7.2  | 6.7 | 8.5  | 7.7  | 7.1  | 6.6 | 8.1  | 7.4 | 6.9  | 6.5 | 7.7  | 7.2 | 6.7  | 6.3 | 6.0 |     |     |  |     |
| 取付高さ   | 器具間隔最大限          |         | 2.5           | 9.0  | 8.3  | 7.7 | 7.2  | 8.8  | 8.2  | 7.6 | 7.2  | 8.4 | 7.9  | 7.4 | 7.0  | 8.1 | 7.6  | 7.2 | 6.9 | 6.5 |     |  |     |
|        | 横方向 (A)          | 縦方向 (B) | 3.0           | 9.3  | 8.7  | 8.1 | 7.7  | 9.1  | 8.5  | 8.0 | 7.6  | 8.7 | 8.2  | 7.8 | 7.4  | 8.3 | 7.9  | 7.6 | 7.3 | 6.9 |     |  |     |
| 1.5m   | 2 m              | 2.19 m  | 4.0           | 9.6  | 9.1  | 8.7 | 8.3  | 9.4  | 9.0  | 8.5 | 8.2  | 9.0 | 8.6  | 8.3 | 8.0  | 8.7 | 8.3  | 8.1 | 7.8 | 7.4 |     |  |     |
| 2      | 2.64             | 2.76    | 5.0           | 9.8  | 9.4  | 9.0 | 8.7  | 9.6  | 9.2  | 8.9 | 8.6  | 9.2 | 8.9  | 8.6 | 8.3  | 8.9 | 8.6  | 8.4 | 8.1 | 7.8 |     |  |     |
| 2.5    | 3.29             | 3.35    | 7.0           | 10.1 | 9.7  | 9.4 | 9.2  | 9.9  | 9.6  | 9.3 | 9.0  | 9.5 | 9.3  | 9.0 | 8.8  | 9.2 | 8.9  | 8.8 | 8.6 | 8.2 |     |  |     |
| 3      | 3.93             | 3.96    | 10.0          | 10.2 | 10.0 | 9.8 | 9.6  | 10.1 | 9.8  | 9.6 | 9.4  | 9.7 | 9.5  | 9.3 | 9.2  | 9.4 | 9.2  | 9.1 | 8.9 | 8.5 |     |  |     |

