

# 屋内照明器具特性

品番 (品名)	NNLK41521J + NNL4500EX										
光源	LED5000_85_5050 x1 5050.0 lm										
管理番号	K0132113 (6) DB1										
BZ分類	BZ6										

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	17 %	室指数																	照明率 ( X0.01)																	ZCM																
下方光束	83 %																																																			
保守率	良 中 否	0.83	0.6	51	38	30	24	49	37	29	24	45	34	28	23	41	32	26	22	19																																
		0.81	0.8	60	48	39	33	57	46	38	32	53	43	36	31	48	40	34	30	26																																
			1.0	66	55	46	40	63	53	45	39	58	49	42	37	53	46	40	35	31																																
		0.77	1.25	72	61	53	47	69	59	51	45	63	55	48	43	58	51	46	41	36																																
下方投影面積	c m <sup>2</sup>	1.5	76	66	58	52	73	64	56	51	67	59	53	48	62	55	50	46	40																																	
		2.0	82	73	66	60	79	71	64	58	72	66	60	55	67	61	57	53	47																																	
取付高さ	器具間隔最大限		2.5	86	78	71	66	82	75	69	64	76	70	65	61	70	65	61	57	51																																
	横方向 (A)	縦方向 (B)	3.0	88	81	75	70	85	79	73	68	78	73	69	65	73	68	65	61	55																																
1.5m	1.98 m	2.16 m	4.0	92	86	81	76	88	83	78	74	82	78	74	70	76	73	69	66	60																																
2	2.61	2.71	5.0	94	89	85	81	90	86	82	78	84	81	77	74	78	75	72	70	63																																
2.5	3.24	3.3	7.0	96	93	89	86	93	90	86	83	87	84	81	79	81	79	76	74	67																																
3	3.87	3.89	10.0	99	96	93	90	95	93	90	88	89	87	85	83	83	82	80	78	71																																

