

# 屋内照明器具特性

品番 (品名)	NNCF22115 ( J YOUJI _ CEILING )										
光源	LED5000_85_1600 x1 1600.0 lm										
管理番号	K0185375 ( 1 ) DB 1										
BZ分類	BZ5										

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	8 %	室指数																	照明率 ( X0.01 )																	ZCM																
下方光束	92 %																																																			
保守率	良 中 否	0.83	0.6	5.5	4.2	3.4	2.9	5.3	4.1	3.4	2.9	5.0	4.0	3.3	2.8	4.7	3.8	3.2	2.8	2.5																																
		0.81	0.8	6.4	5.3	4.5	3.9	6.2	5.2	4.4	3.9	5.9	4.9	4.3	3.8	5.5	4.7	4.1	3.7	3.4																																
		0.77	1.0	7.1	6.0	5.2	4.6	6.9	5.9	5.1	4.6	6.5	5.6	5.0	4.5	6.1	5.4	4.8	4.4	4.1																																
			1.25	7.7	6.7	6.0	5.4	7.5	6.6	5.9	5.3	7.0	6.3	5.7	5.2	6.7	6.0	5.5	5.1	4.7																																
下方投影面積		c m <sup>2</sup>																																																		
等価発光面積		c m <sup>2</sup>																																																		
取付高さ	器具間隔最大限																																																			
	横方向 (A)	縦方向 (B)																																																		
1.5m	2m	1.95m	4.0	9.6	9.1	8.7	8.4	9.4	8.9	8.6	8.2	8.9	8.6	8.3	8.0	8.5	8.2	8.0	7.7	7.3																																
2	2.62	2.53	5.0	9.8	9.4	9.1	8.7	9.6	9.2	8.9	8.6	9.1	8.8	8.6	8.3	8.7	8.5	8.2	8.0	7.6																																
2.5	3.29	3.15	7.0	10.0	9.7	9.5	9.2	9.8	9.5	9.3	9.1	9.4	9.1	8.9	8.7	9.0	8.8	8.6	8.4	8.0																																
3	3.95	3.77	10.0	10.2	10.0	9.8	9.6	10.0	9.8	9.6	9.4	9.6	9.4	9.2	9.1	9.2	9.0	8.9	8.8	8.3																																

