

屋内照明器具特性	
品番 (品名)	NNCF22115 (JYOUJI_WALL)
光源	LED5000_85_1600 x1 1600.0 lm
管理番号	K0185577 (1) DR 1
BZ分類	BZ10/0.7/BZ9

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		50%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		50%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.83	0.6	4.4	3.1	2.3	1.7	4.0	2.8	2.1	1.6	3.2	2.3	1.7	1.3	2.6	1.8	1.4	1.0	0.5	
	中	0.81	0.8	5.2	3.9	3.0	2.4	4.7	3.6	2.8	2.2	3.8	2.9	2.3	1.8	3.0	2.4	1.8	1.5	0.8	
	否	0.77	1.0	5.8	4.5	3.7	3.0	5.2	4.2	3.4	2.8	4.3	3.4	2.8	2.3	3.4	2.7	2.2	1.8	1.0	
	下方投影面積	c m <sup>2</sup>		1.25	6.3	5.2	4.3	3.6	5.8	4.7	4.0	3.3	4.7	3.9	3.3	2.8	3.7	3.1	2.6	2.2	1.3
等価発光面積	c m <sup>2</sup>		1.5	6.7	5.7	4.8	4.2	6.1	5.2	4.4	3.8	5.0	4.3	3.7	3.2	4.0	3.5	3.0	2.6	1.6	
	c m <sup>2</sup>		2.0	7.3	6.4	5.6	5.0	6.7	5.8	5.2	4.6	5.5	4.9	4.3	3.9	4.4	3.9	3.5	3.1	2.0	
取付高さ	器具間隔最大限		2.5	7.7	6.8	6.1	5.5	7.0	6.3	5.7	5.1	5.8	5.3	4.8	4.3	4.7	4.3	3.9	3.6	2.3	
	横方向 (A)	縦方向 (B)	3.0	7.9	7.2	6.6	6.0	7.3	6.6	6.1	5.6	6.1	5.6	5.1	4.7	4.9	4.5	4.2	3.9	2.6	
1.5m	0	1.95m	4.0	8.3	7.7	7.1	6.6	7.7	7.1	6.6	6.2	6.4	6.0	5.6	5.2	5.2	4.9	4.6	4.3	2.9	
2	0	2.57	5.0	8.5	8.0	7.5	7.1	7.9	7.4	7.0	6.6	6.6	6.3	5.9	5.6	5.5	5.2	4.9	4.6	3.2	
2.5	0	3.19	7.0	8.8	8.4	8.0	7.6	8.2	7.8	7.4	7.1	6.9	6.6	6.3	6.1	5.7	5.5	5.3	5.0	3.5	
3	0	3.82	10.0	9.1	8.7	8.4	8.1	8.4	8.1	7.8	7.6	7.1	6.9	6.7	6.5	5.9	5.7	5.6	5.4	3.8	

