

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | NNCF42135 ( J YOUJI _ WALL ) |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_3800 ×1 3800.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0185575 ( 1 ) DR 1          |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ10/0.9/BZ9                 |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |         |         |               |    |      |    |      |    |      |    |      |    |      |    |      |    |      |    |     |    |     |
|--------|---------|---------|---------------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|-----|----|-----|
| 器具効率   | 100 %   | 天井      | 80 %          |    |      |    | 70 % |    |      |    | 50 % |    |      |    | 30 % |    |      |    | 0 % |    |     |
|        |         |         | 反射率           | 壁  | 70   | 50 | 30   | 10 | 70   | 50 | 30   | 10 | 70   | 50 | 30   | 10 | 70   | 50 | 30  | 10 | 0 % |
|        |         |         |               | 床  | 10 % |    |      |    | 10 % |    |      |    | 10 % |    |      |    | 10 % |    |     |    | 0 % |
| 上方光束   | 50 %    | 室指数     | 照明率 ( X0.01 ) |    |      |    |      |    |      |    |      |    |      |    |      |    |      |    | ZCM |    |     |
| 下方光束   | 50 %    |         |               |    |      |    |      |    |      |    |      |    |      |    |      |    |      |    |     |    |     |
| 保守率    | 良       | 0.83    | 0.6           | 43 | 31   | 23 | 17   | 39 | 28   | 21 | 15   | 32 | 23   | 17 | 13   | 25 | 18   | 13 | 10  | 5  |     |
|        | 中       | 0.81    | 0.8           | 52 | 39   | 30 | 24   | 47 | 36   | 28 | 22   | 38 | 29   | 23 | 18   | 30 | 23   | 18 | 14  | 8  |     |
|        | 否       | 0.77    | 1.0           | 57 | 45   | 36 | 30   | 52 | 41   | 33 | 27   | 43 | 34   | 28 | 23   | 34 | 27   | 22 | 18  | 10 |     |
|        |         |         | 1.25          | 63 | 51   | 43 | 36   | 57 | 47   | 39 | 33   | 47 | 39   | 33 | 28   | 37 | 31   | 26 | 22  | 13 |     |
| 下方投影面積 |         |         | 1.5           | 67 | 56   | 48 | 41   | 61 | 52   | 44 | 38   | 50 | 43   | 37 | 32   | 40 | 34   | 30 | 26  | 16 |     |
| 等価発光面積 |         |         | 2.0           | 73 | 63   | 56 | 49   | 67 | 58   | 51 | 46   | 55 | 49   | 43 | 38   | 44 | 39   | 35 | 31  | 20 |     |
| 取付高さ   | 器具間隔最大限 |         | 2.5           | 77 | 68   | 61 | 55   | 70 | 63   | 57 | 51   | 58 | 53   | 47 | 43   | 47 | 43   | 39 | 35  | 23 |     |
|        | 横方向 (A) | 縦方向 (B) | 3.0           | 79 | 72   | 65 | 60   | 73 | 66   | 60 | 55   | 61 | 55   | 51 | 47   | 49 | 45   | 42 | 38  | 25 |     |
| 1.5m   | 0       | 2.12m   | 4.0           | 83 | 77   | 71 | 66   | 76 | 71   | 66 | 61   | 64 | 60   | 56 | 52   | 52 | 49   | 46 | 43  | 29 |     |
| 2      | 0       | 2.7     | 5.0           | 85 | 80   | 75 | 71   | 79 | 74   | 70 | 65   | 66 | 62   | 59 | 56   | 54 | 51   | 49 | 46  | 32 |     |
| 2.5    | 0       | 3.3     | 7.0           | 88 | 84   | 80 | 76   | 82 | 78   | 74 | 71   | 69 | 66   | 63 | 60   | 57 | 55   | 52 | 50  | 35 |     |
| 3      | 0       | 3.91    | 10.0          | 90 | 87   | 84 | 81   | 84 | 81   | 78 | 76   | 71 | 69   | 67 | 65   | 59 | 57   | 56 | 54  | 38 |     |

