

屋内照明器具特性	
品番 (品名)	NNF 4 2 2 4 5 K
光源	LDL40S.N/19/25-K ×2      2500.0 lm
管理番号	K0126286(1)DR1
BZ分類	BZ6/1.4/BZ5/1.8/BZ6/2.3/BZ5 /3.5/BZ6/4.5/BZ5

器具効率	95 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	1 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	94 %	室指数	照明率 ( X0.01 )																ZCM	
保守率	良 0.81 中 0.77 否 0.68	0.6	51	38	31	25	49	38	30	25	47	37	30	25	44	35	29	25	23	
		0.8	60	48	40	34	58	47	40	34	55	46	39	34	53	44	38	33	31	
		1.0	66	55	47	41	64	54	46	41	61	52	45	40	58	50	44	40	37	
		1.25	72	61	54	48	70	60	53	47	67	58	52	47	64	56	51	46	44	
下方投影面積	c m <sup>2</sup>	1.5	76	66	59	53	74	65	58	53	71	63	57	52	67	61	56	51	48	
		2.0	81	73	67	61	80	72	66	61	76	70	64	60	73	67	63	59	56	
取付高さ	器具間隔最大限		2.5	85	78	72	67	83	77	71	66	80	74	69	65	77	72	68	64	61
	横方向 (A)	縦方向 (B)	3.0	88	81	76	71	86	80	75	71	82	78	73	69	79	75	71	68	65
1.5m	2.14 m	2.19 m	4.0	91	86	81	77	89	85	80	77	86	82	78	75	83	80	77	74	71
2	2.83	2.76	5.0	93	89	85	81	91	87	84	81	88	85	82	79	85	82	80	77	74
2.5	3.52	3.36	7.0	96	92	89	86	94	91	88	85	91	88	86	84	88	86	84	82	79
3	4.21	3.96	10.0	97	95	93	91	96	94	92	90	93	91	89	88	90	89	87	86	83

