

屋内照明器具特性

品番 (品名)	NNN02023W		
光源	NNN02023W(30 DEG) x1 500.0 1m		
管理番号	K0122946(4)DD1		
BZ分類	BZ1		

器具効率	101%	天井	80%				70%				50%				30%				0%	
	上方光束 1%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	90	85	82	80	90	85	82	80	88	84	82	80	87	84	82	80	79	
	中 0.63		0.8	94	90	86	84	93	89	86	84	92	88	86	84	91	88	85	83	82
	否 0.56		1.0	97	92	89	87	96	92	89	87	94	91	88	86	93	90	88	86	85
下方投影面積	cm ²	1.25	99	95	92	90	98	94	91	89	96	93	91	89	94	92	90	88	87	
		1.5	100	97	94	92	99	96	93	91	97	95	92	91	96	93	91	90	88	
等価発光面積	cm ²	2.0	102	99	97	95	101	98	96	94	99	97	95	93	97	95	94	92	90	
		2.5	103	101	98	97	102	100	98	96	100	98	96	95	98	96	95	94	92	
取付高さ	器具間隔最大限		3.0	104	102	100	98	103	101	99	97	101	99	97	96	99	97	96	95	93
	横方向 (A)	縦方向 (B)	4.0	105	103	102	100	104	102	101	99	102	100	99	98	100	99	97	96	94
Hm	0.46Hm	0.46Hm	5.0	106	104	103	102	105	103	102	101	102	101	100	99	100	99	98	98	95
			7.0	107	106	104	103	106	104	103	102	103	102	101	101	100	100	99	99	96
			10.0	107	106	106	105	106	105	104	104	104	103	102	102	101	100	100	97	

