

屋内照明器具特性

品番 (品名)	NNN02024B		
光源	NNN02024B (10 DEG) x1 400.0 lm		
管理番号	K0122944 (4) DD1		
BZ分類	BZ1		

器具効率	102%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	102%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	0.6	97	93	91	89	96	93	91	89	95	92	90	89	95	92	90	89	88
	中 0.63		0.8	99	96	93	91	99	95	93	91	97	95	92	91	96	94	92	91	90
	否 0.56		1.0	101	97	95	93	100	97	95	93	99	96	94	92	97	95	93	92	91
下方投影面積 等価発光面積	cm ²	cm ²	1.25	102	99	97	95	101	98	96	94	100	97	95	94	98	96	95	93	92
			1.5	103	100	98	96	102	100	98	96	101	98	97	95	99	97	96	94	93
			2.0	105	102	100	98	104	101	99	98	102	100	98	97	100	99	97	96	94
取付高さ	器具間隔最大限		2.5	106	103	102	100	105	103	101	99	103	101	99	98	101	99	98	97	95
	横方向 (A)	縦方向 (B)	3.0	106	104	103	101	105	103	102	100	103	102	100	99	101	100	99	98	96
Hm	0.24Hm	0.24Hm	4.0	107	106	104	103	106	105	103	102	104	103	102	101	102	101	100	99	97
			5.0	108	106	105	104	107	105	104	103	105	103	102	102	102	101	100	99	97
			7.0	109	108	106	105	107	106	105	105	104	104	103	103	102	102	101	99	98
			10.0	109	108	108	107	108	107	106	106	106	105	104	104	103	103	102	102	99

