

屋内照明器具特性	
品番 (品名)	NNF 4 2 5 6 6
光源	LDL40S.N/14/26(2600A) ×2 2600.0 1 m
管理番号	K0139060(0)DB1
BZ分類	BZ5

器具効率	56%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	1%	床	10%				10%				10%				10%				0%	
下方光束	55%	室指数	照明率 (X0.01) ZCM																	
保守率	良 0.77 中 0.72 否 0.68	0.6	31	24	20	17	30	24	19	17	29	23	19	16	27	22	19	16	15	
		0.8	36	30	25	22	36	29	25	22	34	29	25	22	32	28	24	22	20	
		1.0	40	34	30	26	39	33	29	26	37	32	29	26	36	31	28	26	24	
		1.25	43	38	34	30	42	37	33	30	40	36	33	30	39	35	32	29	28	
下方投影面積	c m ²	1.5	46	41	37	33	45	40	36	33	43	39	35	33	41	38	35	32	31	
		2.0	49	45	41	38	48	44	41	38	46	42	40	37	44	41	39	37	35	
取付高さ	器具間隔最大限		2.5	51	47	44	41	50	46	43	41	48	45	42	40	46	44	41	40	38
	横方向 (A)	縦方向 (B)	3.0	52	49	46	44	51	48	46	43	49	47	44	43	47	45	43	42	40
1.5m	1.96 m	2.16 m	4.0	54	51	49	47	53	51	48	46	51	49	47	46	49	48	46	45	43
2	2.59	2.72	5.0	55	53	51	49	54	52	50	49	52	51	49	48	51	49	48	47	45
2.5	3.22	3.31	7.0	56	55	53	52	55	54	52	51	54	52	51	50	52	51	50	49	47
3	3.84	3.92	10.0	57	56	55	54	56	55	54	53	55	54	53	52	53	52	52	51	49

