

屋内照明器具特性

品番 (品名)	NNF 4 2 5 6 7									
光源	LDL40S.N/14/26(2600A) ×2 2600.0 1 m									
管理番号	K0139059(0)DB1									
BZ分類	BZ5									

器具効率	51 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	1 %	室指数																	照明率 (X0.01)																	ZCM																
下方光束	50 %																																																			
保守率	良 中 否	0.77	0.6	2.8	2.2	1.8	1.5	2.8	2.2	1.8	1.5	2.6	2.1	1.8	1.5	2.5	2.1	1.7	1.5	1.4																																
		0.72	0.8	3.3	2.8	2.4	2.1	3.3	2.7	2.3	2.1	3.1	2.6	2.3	2.0	3.0	2.6	2.3	2.0	1.9																																
		0.68	1.0	3.7	3.1	2.7	2.4	3.6	3.1	2.7	2.4	3.4	3.0	2.7	2.4	3.3	2.9	2.6	2.4	2.3																																
			1.25	4.0	3.5	3.1	2.8	3.9	3.4	3.1	2.8	3.7	3.3	3.0	2.8	3.6	3.2	3.0	2.7	2.6																																
下方投影面積		c m ²																																																		
等価発光面積		c m ²																																																		
取付高さ	器具間隔最大限																																																			
	横方向 (A)	縦方向 (B)																																																		
1.5m	1.94 m	2.15 m	4.0	5.0	4.7	4.5	4.3	4.0	4.7	4.4	4.2	4.0	4.5	4.3	4.1	3.9	4.4	4.2	4.0	3.9	3.7																															
2	2.57	2.72	5.0	5.1	4.9	4.7	4.5	5.0	4.8	4.6	4.5	4.8	4.7	4.5	4.4	4.7	4.5	4.4	4.3	4.2																																
2.5	3.19	3.31	7.0	5.2	5.0	4.9	4.8	5.1	5.0	4.8	4.7	4.9	4.8	4.7	4.6	4.8	4.7	4.6	4.5	4.4																																
3	3.81	3.91	10.0	5.3	5.2	5.1	5.0	5.2	5.1	5.0	4.9	5.0	5.0	4.9	4.8	4.9	4.8	4.8	4.7	4.5																																

