

屋内照明器具特性

| | | | | | | | | | | |
|---------|---|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | NNF 4 2 6 6 6 | | | | | | | | | |
| 光源 | LDL40S.N/14/26(2600A) ×2 2600.0 1m | | | | | | | | | |
| 管理番号 | K0126620(8)DB1 | | | | | | | | | |
| BZ分類 | BZ5/0.7/BZ4 | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--------|------------------|---------|------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|----|--------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|-----|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 器具効率 | 90% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 上方光束 | 0% | 室指数 | | | | | | | | | | | | | | | | | | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | ZCM | | | | | | | | | | | | | | | | | |
| 下方光束 | 90% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 保守率 | 良 中 否 | 0.81 | 0.6 | 51 | 41 | 34 | 29 | 50 | 40 | 33 | 29 | 48 | 39 | 33 | 29 | 46 | 38 | 33 | 28 | 27 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 0.77 | 0.8 | 61 | 51 | 44 | 39 | 60 | 50 | 44 | 39 | 57 | 49 | 43 | 39 | 55 | 48 | 42 | 38 | 36 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | 1.0 | 67 | 58 | 51 | 46 | 66 | 57 | 51 | 46 | 63 | 56 | 50 | 46 | 61 | 54 | 49 | 45 | 43 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 0.68 | 1.25 | 73 | 64 | 58 | 53 | 71 | 63 | 58 | 53 | 69 | 62 | 57 | 52 | 66 | 60 | 56 | 52 | 50 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 下方投影面積 | c m ² | 1.5 | 76 | 69 | 63 | 58 | 75 | 68 | 62 | 58 | 72 | 66 | 61 | 57 | 70 | 65 | 60 | 57 | 55 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 2.0 | 81 | 75 | 70 | 66 | 80 | 74 | 69 | 65 | 77 | 72 | 68 | 65 | 75 | 71 | 67 | 64 | 62 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 等価発光面積 | c m ² | 2.5 | 84 | 79 | 75 | 71 | 83 | 78 | 74 | 70 | 80 | 76 | 73 | 70 | 78 | 75 | 71 | 69 | 66 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 3.0 | 87 | 82 | 78 | 75 | 85 | 81 | 77 | 74 | 83 | 79 | 76 | 73 | 80 | 77 | 75 | 72 | 70 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 取付高さ | 器具間隔最大限 | | 4.0 | 89 | 86 | 82 | 80 | 88 | 85 | 82 | 79 | 85 | 83 | 80 | 78 | 83 | 81 | 79 | 77 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 横方向 (A) | 縦方向 (B) | 5.0 | 91 | 88 | 85 | 83 | 90 | 87 | 84 | 82 | 87 | 85 | 83 | 81 | 85 | 83 | 81 | 79 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5m | 2.09m | 2.18m | 7.0 | 93 | 90 | 88 | 87 | 91 | 89 | 88 | 86 | 89 | 87 | 86 | 84 | 87 | 85 | 84 | 83 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | 2.76 | 2.75 | 10.0 | 94 | 92 | 91 | 90 | 93 | 91 | 90 | 89 | 91 | 89 | 88 | 87 | 88 | 87 | 86 | 86 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.5 | 3.43 | 3.34 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | 4.09 | 3.94 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

