

屋内照明器具特性	
品番 (品名)	NNN11111
光源	LDA5L-D-G-E17/S/Z4 ×1 440.0 l m
管理番号	K0173114(0)DB1
BZ分類	BZ9/0.7/BZ8

器具効率	53%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	25%	床	10%				10%				10%				10%				0%	
下方光束	28%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.69	0.6	2.4	1.7	1.3	1.0	2.2	1.6	1.2	0.9	1.8	1.3	1.0	0.8	1.5	1.1	0.8	0.6	0.4	
	中 0.67	0.8	2.8	2.2	1.7	1.4	2.6	2.0	1.6	1.3	2.2	1.7	1.4	1.1	1.8	1.4	1.1	0.9	0.6	
	否 0.63	1.0	3.1	2.5	2.1	1.7	2.9	2.3	1.9	1.6	2.4	2.0	1.6	1.4	2.0	1.6	1.4	1.1	0.7	
下方投影面積	cm ²	1.25	3.4	2.8	2.4	2.1	3.2	2.6	2.2	1.9	2.6	2.2	1.9	1.7	2.2	1.8	1.6	1.4	0.9	
		1.5	3.7	3.1	2.7	2.3	3.4	2.9	2.5	2.2	2.8	2.4	2.1	1.9	2.3	2.0	1.8	1.6	1.1	
等価発光面積	cm ²	2.0	4.0	3.5	3.1	2.8	3.6	3.2	2.9	2.6	3.1	2.7	2.5	2.2	2.5	2.3	2.1	1.9	1.3	
		2.5	4.1	3.7	3.4	3.1	3.8	3.5	3.1	2.9	3.2	2.9	2.7	2.5	2.7	2.5	2.3	2.1	1.5	
取付高さ	器具間隔最大限		3.0	4.3	3.9	3.6	3.3	4.0	3.6	3.3	3.1	3.4	3.1	2.9	2.7	2.8	2.6	2.4	1.6	
	横方向 (A)	縦方向 (B)	4.0	4.5	4.2	3.9	3.6	4.1	3.9	3.6	3.4	3.5	3.3	3.1	2.9	3.0	2.8	2.6	1.8	
Hm	1.79Hm	1.70Hm	5.0	4.6	4.3	4.1	3.9	4.3	4.0	3.8	3.6	3.6	3.5	3.3	3.1	3.1	2.9	2.8	1.9	
			7.0	4.7	4.5	4.3	4.2	4.4	4.2	4.0	3.9	3.8	3.6	3.5	3.4	3.2	3.1	3.0	2.1	
			10.0	4.9	4.7	4.5	4.4	4.5	4.4	4.2	4.1	3.9	3.8	3.7	3.6	3.3	3.2	3.1	2.3	

