

屋内照明器具特性

品番 (品名)	HH- X S F 0 0 0 1 L																		
光源	LDA5 L - G / K40 / BT / W ×1 550.0 lm																		
管理番号	K0152753 (0) DB 1																		
B Z 分類	BZ10																		

器具効率		9 2 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		6 4 %	室 指 数	照 明 率 (X 0 . 0 1) Z C M																		
下方光束		2 8 %																				
保守率	良	0 . 6 3	0 . 6	3 9	2 8	2 1	1 6	3 5	2 5	1 9	1 5	2 6	1 9	1 4	1 1	1 8	1 3	1 0	7	1		
	中	0 . 6	0 . 8	4 6	3 5	2 8	2 3	4 1	3 1	2 5	2 0	3 1	2 4	1 9	1 5	2 2	1 7	1 3	1 1	3		
	否	0 . 5 6	1 . 0	5 1	4 1	3 3	2 8	4 5	3 6	3 0	2 5	3 4	2 8	2 3	1 9	2 4	2 0	1 6	1 3	4		
下方投影面積		c m ²	1 . 2 5	5 6	4 6	3 9	3 3	5 0	4 1	3 5	3 0	3 8	3 2	2 7	2 3	2 7	2 2	1 9	1 6	5		
			1 . 5	6 0	5 1	4 3	3 8	5 3	4 5	3 9	3 4	4 0	3 5	3 0	2 6	2 9	2 5	2 1	1 8	6		
等価発光面積		c m ²	2 . 0	6 5	5 7	5 0	4 5	5 7	5 1	4 5	4 0	4 4	3 9	3 5	3 1	3 2	2 8	2 5	2 2	9		
取付	器具間隔最大限		2 . 5	6 8	6 1	5 5	5 0	6 0	5 4	4 9	4 5	4 7	4 2	3 8	3 5	3 4	3 0	2 8	2 5	1 0		
高さ	横方向 (A) 縦方向 (B)		3 . 0	7 0	6 4	5 8	5 3	6 3	5 7	5 2	4 8	4 8	4 4	4 1	3 7	3 5	3 2	3 0	2 7	1 2		
H m	0 . 0 0 H m	0 . 0 0 H m	4 . 0	7 3	6 8	6 3	5 9	6 6	6 1	5 7	5 3	5 1	4 8	4 4	4 2	3 7	3 5	3 3	3 0	1 4		
			5 . 0	7 5	7 1	6 6	6 3	6 7	6 3	6 0	5 7	5 3	5 0	4 7	4 4	3 9	3 7	3 5	3 3	1 5		
			7 . 0	7 8	7 4	7 1	6 8	7 0	6 7	6 4	6 1	5 5	5 2	5 0	4 8	4 1	3 9	3 7	3 6	1 7		
			1 0 . 0	7 9	7 7	7 4	7 2	7 2	6 9	6 7	6 5	5 7	5 5	5 3	5 1	4 2	4 1	4 0	3 8	1 9		

