

屋内照明器具特性	
品番 (品名)	NNN11320K
光源	LDA5L-D-G-E17/S/Z4 ×3      440.0 l m
管理番号	K0172936(0)DB1
BZ分類	BZ6

器具効率	68 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	29 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	39 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.63	0.6	3.3	2.5	1.9	1.6	3.0	2.3	1.8	1.5	2.6	2.0	1.6	1.3	2.2	1.7	1.4	1.2	8
	中	0.6	0.8	3.9	3.1	2.5	2.1	3.6	2.9	2.4	2.0	3.1	2.5	2.1	1.8	2.6	2.1	1.8	1.6	1.2
	否	0.56	1.0	4.3	3.5	3.0	2.6	4.0	3.3	2.8	2.4	3.4	2.9	2.5	2.2	2.9	2.4	2.1	1.9	1.4
			1.25	4.6	3.9	3.4	3.0	4.3	3.7	3.2	2.8	3.7	3.2	2.8	2.5	3.1	2.7	2.4	2.2	1.7
下方投影面積		cm <sup>2</sup>	1.5	4.9	4.3	3.8	3.4	4.6	4.0	3.5	3.2	3.9	3.5	3.1	2.8	3.3	3.0	2.7	2.4	1.8
等価発光面積		cm <sup>2</sup>	2.0	5.3	4.7	4.3	3.9	4.9	4.4	4.0	3.7	4.2	3.8	3.5	3.2	3.6	3.3	3.0	2.8	2.1
取付高さ	器具間隔最大限		2.5	5.5	5.0	4.6	4.3	5.1	4.7	4.3	4.0	4.4	4.1	3.8	3.5	3.8	3.5	3.3	3.1	2.3
	横方向 (A)	縦方向 (B)	3.0	5.7	5.3	4.9	4.6	5.3	4.9	4.6	4.3	4.6	4.3	4.0	3.8	3.9	3.7	3.5	3.3	2.5
1.5m	1.99 m	1.99 m	4.0	5.9	5.6	5.2	5.0	5.5	5.2	4.9	4.7	4.8	4.5	4.3	4.1	4.1	3.9	3.7	3.6	2.7
2	2.65	2.66	5.0	6.0	5.7	5.5	5.2	5.7	5.4	5.1	4.9	4.9	4.7	4.5	4.3	4.2	4.1	3.9	3.8	2.9
2.5	3.32	3.32	7.0	6.2	6.0	5.8	5.6	5.8	5.6	5.4	5.2	5.1	4.9	4.8	4.6	4.4	4.2	4.1	4.0	3.1
3	3.98	3.98	10.0	6.3	6.2	6.0	5.8	6.0	5.8	5.7	5.5	5.2	5.1	5.0	4.9	4.5	4.4	4.3	4.2	3.3

