

屋内照明器具特性	
品番 (品名)	HH- CF 0 6 9 4 AT
光源	LED6200_70_3200 ×1 3200.0 lm
管理番号	K0163083 (0) D 1
B Z 分類	BZ6

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) Z CM																				
保守率		良 中 否	0.63	0.6	50	37	29	24	47	35	28	23	41	32	26	21	37	29	23	19	16				
			0.6	0.8	59	47	38	32	55	44	37	31	49	40	34	29	44	36	31	27	22				
			0.56	1.0	65	54	45	39	61	51	43	38	55	46	40	35	48	42	36	32	27				
				1.25	71	60	52	46	67	57	50	44	60	52	46	41	53	47	42	38	31				
下方投影面積		cm ²	1.5	75	65	58	52	71	62	55	50	63	56	50	46	56	51	46	42	35					
			等価発光面積		cm ²	2.0	81	72	65	60	76	69	63	58	68	62	57	53	61	56	52	49	41		
取付 高さ	器具間隔最大限		2.5	84	77	71	66	80	73	68	63	72	67	62	58	64	60	57	53	45					
	横方向 (A) 縦方向 (B)		3.0	87	80	75	70	83	77	72	67	74	70	66	62	67	63	60	57	48					
H m	1.35 H m 1.35 H m		4.0	90	85	80	76	86	81	77	73	78	74	71	67	70	67	64	62	53					
			5.0	92	88	84	80	88	84	81	77	80	77	74	71	72	69	67	65	56					
			7.0	95	92	88	86	91	88	85	82	82	80	78	75	74	73	71	69	59					
			10.0	97	94	92	90	93	90	88	86	84	83	81	79	76	75	74	72	62					

