

屋内照明器具特性	
品番 (品名)	LAMP_BH100-110V100W.C
光源	BH100-110V100W.C ×1 1090.0lm
管理番号	K0019411 (*) DJ 1
BZ分類	BZ9/0.7/BZ8

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		4 9 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		5 1 %																				
保守率		良 中 否	0 . 8	0 . 6	4 5	3 3	2 5	1 9	4 1	3 0	2 3	1 8	3 4	2 5	1 9	1 5	2 7	2 1	1 6	1 2	7	
			0 . 7 7	0 . 8	5 3	4 1	3 3	2 7	4 9	3 8	3 0	2 5	4 0	3 2	2 6	2 1	3 3	2 6	2 1	1 7	1 1	
			0 . 7 3	1 . 0	5 9	4 8	3 9	3 3	5 4	4 4	3 6	3 1	4 5	3 7	3 1	2 6	3 6	3 0	2 5	2 1	1 4	
				1 . 2 5	6 5	5 4	4 6	3 9	5 9	5 0	4 2	3 6	4 9	4 2	3 6	3 1	4 0	3 4	2 9	2 6	1 7	
下方投影面積		c m ²	1 . 5	6 9	5 9	5 1	4 4	6 3	5 4	4 7	4 1	5 2	4 5	4 0	3 5	4 3	3 7	3 3	2 9	1 9		
等価発光面積		c m ²	2 . 0	7 4	6 6	5 8	5 2	6 8	6 1	5 4	4 9	5 7	5 1	4 6	4 1	4 7	4 2	3 8	3 4	2 3		
取付 高さ	器具間隔最大限		2 . 5	7 8	7 0	6 4	5 8	7 2	6 5	5 9	5 4	6 0	5 5	5 0	4 6	4 9	4 5	4 2	3 8	2 6		
	横方向 (A)		縦方向 (B)		3 . 0	8 1	7 4	6 8	6 2	7 4	6 8	6 3	5 8	6 3	5 8	5 3	4 9	5 1	4 8	4 4	4 1	2 8
H m	1 . 8 0 H m	1 . 8 0 H m	4 . 0	8 4	7 8	7 3	6 8	7 8	7 3	6 8	6 4	6 6	6 2	5 8	5 5	5 4	5 1	4 8	4 6	4 6	3 2	
			5 . 0	8 6	8 1	7 7	7 3	8 0	7 5	7 1	6 8	6 8	6 4	6 1	5 8	5 6	5 3	5 1	4 9	3 4		
			7 . 0	8 9	8 5	8 1	7 8	8 3	7 9	7 6	7 3	7 0	6 7	6 5	6 2	5 9	5 6	5 4	5 2	3 8		
			1 0 . 0	9 1	8 8	8 5	8 3	8 5	8 2	8 0	7 7	7 2	7 0	6 8	6 6	6 1	5 9	5 7	5 6	4 0		

