

屋内照明器具特性

品番 (品名)	NNCF40735J (J YOUJI)														
光源	LED5000_85_3000 ×1 3000.0 lm														
管理番号	K0169459 (1) DR 1														
BZ分類	BZ7 / 0.7 / BZ6														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %			
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束	51 %	室指数	照明率 (X0.01)																			ZCM
下方光束	49 %																					
保守率	良	0.83	0.6	47	35	27	22	43	32	25	21	36	27	22	18	29	23	18	15	10		
	中	0.81	0.8	56	44	36	30	51	41	34	28	42	34	29	24	34	28	24	21	14		
	否	0.77	1.0	62	51	43	37	56	47	40	34	47	39	34	30	38	33	28	25	17		
			1.25	67	57	49	43	62	53	46	40	51	44	39	35	42	37	33	29	20		
下方投影面積			1.5	71	62	54	49	65	57	51	45	55	48	43	39	45	40	36	33	23		
			2.0	76	68	62	56	70	63	58	53	59	54	49	45	48	44	41	38	27		
取付高さ	器具間隔最大限		2.5	80	73	67	62	74	68	62	58	62	57	53	50	51	48	44	42	29		
	横方向 (A)	縦方向 (B)	3.0	82	76	71	66	76	71	66	62	64	60	56	53	53	50	47	45	32		
1.5m	2.37 m	2.18 m	4.0	86	81	76	72	79	75	71	67	67	64	61	58	56	53	51	48	35		
2	3.12	2.73	5.0	88	83	79	76	81	77	74	71	69	66	63	61	57	55	53	51	37		
2.5	3.87	3.31	7.0	90	87	84	81	84	81	78	75	71	69	67	65	59	58	56	54	39		
3	4.63	3.9	10.0	92	90	87	85	85	83	81	79	73	71	70	68	61	60	58	57	41		

