

# 屋内照明器具特性

品番 (品名)	NNLK42762J + NNL4300ENT + FS															
光源	LED5000_85_1970 x1 1970.0 lm															
管理番号	K0132587 (3) DB1															
BZ分類	BZ3 / 0.7 / BZ2															

器具効率	99 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	99 %		床	10 %				10 %				10 %				10 %				0 %
室指数	照明率 ( X0.01 ) ZCM																			
保守率	良	0.81	0.6	66	56	49	45	65	55	49	45	63	54	49	45	61	54	48	45	43
	中	0.77	0.8	76	68	62	57	75	67	61	57	73	66	61	57	71	65	60	57	55
	否	0.68	1.0	83	75	69	65	81	74	69	65	79	73	68	65	77	72	68	64	63
			1.25	88	81	76	72	87	80	76	72	84	79	75	71	82	78	74	71	69
下方投影面積			1.5	91	85	81	77	90	84	80	77	87	83	79	76	85	81	78	75	73
			2.0	95	90	87	83	94	90	86	83	92	88	85	82	89	86	84	81	79
取付高さ	器具間隔最大限		2.5	98	94	90	87	96	93	90	87	94	91	88	86	92	89	87	85	83
	横方向 (A)	縦方向 (B)	3.0	99	96	93	90	98	95	92	90	96	93	91	89	93	91	89	88	85
1.5m	1.92 m	2.02 m	4.0	101	99	96	94	100	98	95	93	98	96	94	92	96	94	92	91	89
2	2.55	2.55	5.0	103	100	98	97	101	99	97	96	99	97	96	94	97	95	94	93	90
2.5	3.17	3.09	7.0	104	102	101	99	103	101	100	99	100	99	98	97	98	97	96	95	93
3	3.79	3.65	10.0	105	104	103	102	104	103	102	101	101	101	100	99	99	99	98	97	94

