

# 屋内照明器具特性

品番 (品名)	NNF 4 1 0 3 0 J														
光源	LDL40S . N / 29 / 31 - 9 ( 3 1 5 0 A ) × 1 3 1 5 0 . 0 1 m														
管理番号	K0126617 ( 7 ) DB 1														
B Z 分類	B Z 6														

器具効率	98 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	14 %	室指数	照明率 ( X 0 . 0 1 )															Z C M			
下方光束	84 %																				
保守率	良 0.93 中 0.9 否 0.86	0.6	51	38	30	25	48	37	30	24	45	35	28	23	41	33	27	22	20		
		0.8	60	48	39	34	57	46	39	33	53	43	37	32	49	41	35	30	27		
		1.0	66	54	46	40	63	53	45	39	58	49	43	38	54	46	41	36	32		
		1.25	71	61	53	47	69	59	52	46	63	55	49	44	59	52	47	42	38		
下方投影面積	c m <sup>2</sup>	1.5	76	66	58	52	73	64	57	51	67	60	54	49	62	56	51	47	42		
		2.0	81	73	66	60	78	70	64	59	72	66	61	56	67	62	57	54	48		
取付高さ	器具間隔最大限		2.5	85	77	71	66	82	75	69	64	76	70	65	61	71	66	62	58	53	
	横方向 ( A )	縦方向 ( B )	3.0	87	81	75	70	84	78	73	68	78	74	69	65	73	69	65	62	56	
1.5m	2.17 m	2.11 m	4.0	91	85	80	76	88	83	78	74	82	78	74	71	76	73	70	67	61	
2	2.86	2.67	5.0	93	88	84	80	90	86	82	78	84	81	77	74	79	76	73	71	65	
2.5	3.56	3.24	7.0	95	92	88	85	92	89	86	83	87	84	81	79	81	79	77	75	69	
3	4.24	3.83	10.0	97	95	92	90	94	92	90	87	89	87	85	83	84	82	80	79	72	

