

# 屋内照明器具特性

品番 (品名)	NNLK41509 + NNL4300EX	
光源	LED5000_85_3200 ×1	3200.0 lm
管理番号	K0130920 ( * ) DB 1	
BZ分類	BZ5	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	5 %	反射率	床	10 %				10 %				10 %				10 %				0 %			
下方光束	95 %		室指数	照明率 ( X0.01 )																			
保守率	良	0.83	0.6	55	42	34	29	53	42	34	29	50	40	33	28	48	39	32	28	26			
	中	0.81	0.8	65	53	45	39	63	52	44	38	59	50	43	38	56	48	42	37	35			
	否	0.77	1.0	71	60	52	46	69	59	51	45	65	57	50	45	62	55	49	44	41			
			1.25	77	67	59	53	75	65	58	53	71	63	57	52	68	61	55	51	48			
下方投影面積	c m <sup>2</sup>		1.5	81	72	64	59	79	70	64	58	75	68	62	57	71	65	60	56	53			
	等価発光面積		c m <sup>2</sup>	2.0	87	79	72	67	85	77	71	66	81	74	69	65	77	72	67	63	60		
取付高さ	器具間隔最大限		2.5	90	83	78	73	88	82	76	72	84	79	74	70	81	76	72	69	65			
	横方向 (A)	縦方向 (B)	3.0	93	87	82	77	91	85	80	76	87	82	78	74	83	79	76	73	69			
1.5m	1.99 m	2.16 m	4.0	96	91	87	83	94	90	85	82	90	86	83	80	87	83	81	78	74			
2	2.62	2.73	5.0	98	94	90	87	96	92	89	86	92	89	86	83	89	86	84	81	77			
2.5	3.26	3.31	7.0	100	97	94	92	99	96	93	90	95	92	90	88	91	89	87	86	82			
3	3.89	3.91	10.0	102	100	98	96	100	98	96	94	97	95	93	92	93	92	91	89	85			

