

屋内照明器具特性

品番 (品名)	NTS32008W+NTS92201+NTS91	
光源	LED3000_70_845 ×1	845.0 1m
管理番号	K0168007(1)DJ1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%		
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10			
上方光束	0%	反射率	壁	床	照明率 (X0.01)																ZCM
下方光束	100%	室指数																			
保守率	良 0.63	0.6	0.6	76	68	63	59	75	67	63	59	73	67	62	59	72	66	62	59	58	
	中 0.6	0.6	0.8	84	77	72	69	83	76	72	69	81	75	71	68	79	75	71	68	67	
	否 0.56	0.6	1.0	89	83	78	75	88	82	78	75	86	81	77	74	84	80	77	74	72	
下方投影面積	cm ²	1.25	93	88	83	80	92	87	83	80	90	86	82	79	88	84	81	79	77		
		1.5	96	91	87	84	95	90	87	84	92	89	86	83	90	87	85	83	81		
等価発光面積	cm ²	2.0	99	95	92	89	98	94	91	89	96	93	90	88	94	91	89	87	85		
		2.5	101	98	95	93	100	97	94	92	98	95	93	91	96	94	92	90	88		
取付高さ	器具間隔最大限		3.0	102	99	97	95	101	99	96	94	99	97	95	93	97	95	94	92	90	
	横方向 (A)	縦方向 (B)	4.0	104	102	100	98	103	101	99	97	100	99	97	96	98	97	96	95	92	
Hm	0.67Hm	0.67Hm	5.0	105	103	101	100	104	102	101	99	101	100	99	98	99	98	97	96	94	
			7.0	106	105	103	102	105	104	102	101	103	102	101	100	100	100	99	98	96	
			10.0	107	106	105	104	106	105	104	103	103	103	102	101	101	101	100	100	97	

