

屋内照明器具特性

品番 (品名)	NNF 4 2 0 4 5 J	
光源	LDL40S. WW/ 27 / 20 (2000 A) × 2 2000.0 1 m	
管理番号	K0124923 (1) DR 1	
BZ分類	BZ6	

器具効率	99 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		11 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		88 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.93	0.6	5.2	4.0	3.2	2.6	5.0	3.9	3.1	2.6	4.7	3.7	3.0	2.5	4.4	3.5	2.9	2.4	2.2	
	中	0.9	0.8	6.1	4.9	4.1	3.5	5.9	4.8	4.0	3.5	5.5	4.6	3.9	3.4	5.1	4.3	3.7	3.3	2.9	
	否	0.86	1.0	6.8	5.6	4.8	4.2	6.5	5.5	4.7	4.1	6.1	5.2	4.5	4.0	5.7	4.9	4.3	3.9	3.5	
			1.25	7.3	6.3	5.5	4.9	7.1	6.1	5.4	4.8	6.6	5.8	5.2	4.6	6.2	5.5	4.9	4.5	4.1	
下方投影面積	c m ²		1.5	7.7	6.8	6.0	5.4	7.5	6.6	5.9	5.3	7.0	6.2	5.6	5.1	6.5	5.9	5.4	5.0	4.5	
	等価発光面積		c m ²	2.0	8.3	7.5	6.8	6.2	8.0	7.3	6.6	6.1	7.5	6.9	6.3	5.9	7.1	6.5	6.1	5.7	5.2
取付高さ	器具間隔最大限		2.5	8.7	7.9	7.3	6.8	8.4	7.7	7.1	6.7	7.9	7.3	6.8	6.4	7.4	6.9	6.5	6.2	5.7	
	横方向 (A)	縦方向 (B)	3.0	8.9	8.3	7.7	7.2	8.7	8.1	7.5	7.1	8.1	7.6	7.2	6.8	7.7	7.2	6.9	6.5	6.0	
1.5m	2.1 m	2.11 m	4.0	9.3	8.7	8.3	7.8	9.0	8.5	8.1	7.7	8.5	8.1	7.7	7.4	8.0	7.7	7.4	7.1	6.5	
2	2.77	2.65	5.0	9.5	9.0	8.6	8.2	9.2	8.8	8.4	8.1	8.7	8.4	8.0	7.7	8.2	7.9	7.7	7.4	6.9	
2.5	3.45	3.21	7.0	9.7	9.4	9.0	8.7	9.5	9.1	8.8	8.6	9.0	8.7	8.4	8.2	8.5	8.3	8.1	7.9	7.3	
3	4.11	3.79	10.0	9.9	9.7	9.4	9.2	9.7	9.4	9.2	9.0	9.2	9.0	8.8	8.6	8.7	8.5	8.4	8.2	7.7	

