

屋内照明器具特性

品番 (品名)	NNLK41713 + NNL4300BLC										
光源	LED3000_85_2020 x1 2020.0lm										
管理番号	K0129807 (7) DB1										
BZ分類	BZ5 / 0.7 / BZ4										

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	100%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	58	46	39	33	57	46	38	33	54	44	38	33	52	43	37	33	31
	中	0.77	0.8	68	57	50	44	67	57	49	44	64	55	49	44	62	54	48	44	42
	否	0.68	1.0	75	65	58	52	74	64	57	52	71	63	56	52	68	61	56	51	49
			1.25	81	72	65	60	80	71	65	60	77	69	64	59	74	68	63	59	56
下方投影面積			1.5	85	77	71	65	84	76	70	65	81	74	69	64	78	72	68	64	62
等価発光面積			2.0	91	84	78	74	89	83	78	73	86	81	76	72	83	79	75	72	69
取付高さ	器具間隔最大限		2.5	94	88	83	79	92	87	83	79	90	85	81	78	87	83	80	77	74
	横方向 (A)	縦方向 (B)	3.0	96	91	87	83	95	90	86	83	92	88	85	81	89	86	83	80	78
1.5m	2m	2.21m	4.0	99	95	92	89	98	94	91	88	95	92	89	87	92	90	87	85	83
2	2.65	2.79	5.0	101	98	95	92	100	97	94	91	97	94	92	90	94	92	90	88	86
2.5	3.3	3.4	7.0	103	101	98	96	102	99	97	95	99	97	95	94	97	95	94	92	89
3	3.95	4.02	10.0	105	103	101	100	103	102	100	99	101	99	98	97	98	97	96	95	92

