

# 屋内照明器具特性

品番 (品名)	NNN21970														
光源	NNN21970 ×1					63.0 lm									
管理番号	K0112762(0)DD1														
BZ分類	BZ2														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (×0.01) ZCM																		
下方光束	100%																				
保守率	良 中 否	0.67	0.6	70	60	54	50	68	60	54	50	67	59	54	50	65	58	53	50	48	
		0.63	0.8	79	70	64	60	77	70	64	60	75	68	64	60	73	67	63	60	58	
			1.0	84	77	71	67	83	76	71	67	81	75	70	67	79	73	69	66	65	
		0.56	1.25	89	82	77	73	88	81	77	73	85	80	76	73	83	79	75	72	70	
下方投影面積	c m <sup>2</sup>	1.5	92	86	81	78	91	85	81	77	88	84	80	77	86	82	79	76	74		
		2.0	96	91	87	84	95	90	86	83	92	88	85	83	90	87	84	82	80		
取付高さ	器具間隔最大限		2.5	98	94	91	88	97	93	90	87	95	91	89	86	92	90	87	85	83	
	横方向 (A)	縦方向 (B)	3.0	100	96	93	91	99	95	93	90	96	94	91	89	94	92	90	88	86	
H m	1.06 H m	1.06 H m	4.0	102	99	97	95	101	98	96	94	98	96	94	93	96	94	93	91	89	
			5.0	103	101	99	97	102	100	98	96	100	98	96	95	97	96	95	93	91	
			7.0	105	103	101	100	103	102	100	99	101	100	99	97	99	98	97	96	93	
			10.0	106	104	103	102	104	103	102	101	102	101	100	100	100	99	98	98	95	

