

屋内照明器具特性	
品番 (品名)	NNN12310K
光源	LDA8L-D-G-E17/S/Z6 ×1 760.0 l m
管理番号	K0172937(0)DB1
BZ分類	BZ9/4.5/BZ8/8.5/BZ9

器具効率	72%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	31%	床	10%				10%				10%				10%				0%	
下方光束	41%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	3.2	2.3	1.7	1.3	3.0	2.1	1.6	1.2	2.5	1.8	1.4	1.0	2.0	1.5	1.1	9	5
	中	0.6	0.8	3.8	2.9	2.3	1.8	3.5	2.7	2.1	1.7	3.0	2.3	1.8	1.5	2.4	1.9	1.5	12	8
	否	0.56	1.0	4.3	3.4	2.7	2.3	3.9	3.1	2.5	2.1	3.3	2.7	2.2	1.8	2.7	2.2	1.8	15	10
			1.25	4.7	3.8	3.2	2.7	4.3	3.5	3.0	2.5	3.6	3.0	2.6	2.2	3.0	2.5	2.1	18	12
下方投影面積	cm ²	1.5	5.0	4.2	3.6	3.1	4.6	3.9	3.3	2.9	3.9	3.3	2.9	2.5	3.2	2.8	2.4	2.1	14	
等価発光面積		2.0	5.4	4.7	4.1	3.7	5.0	4.4	3.8	3.4	4.2	3.7	3.3	3.0	3.5	3.1	2.8	2.5	18	
取付高さ	器具間隔最大限		2.5	5.6	5.0	4.5	4.1	5.2	4.7	4.2	3.8	4.4	4.0	3.6	3.3	3.7	3.4	3.1	2.8	2.0
	横方向 (A)	縦方向 (B)	3.0	5.8	5.3	4.8	4.4	5.4	4.9	4.5	4.1	4.6	4.2	3.9	3.6	3.9	3.6	3.3	3.1	2.2
Hm	1.78Hm	1.78Hm	4.0	6.1	5.6	5.2	4.9	5.7	5.3	4.9	4.6	4.9	4.5	4.2	4.0	4.1	3.8	3.6	2.5	
			5.0	6.3	5.9	5.5	5.2	5.8	5.5	5.2	4.9	5.0	4.7	4.5	4.2	4.3	4.0	3.8	2.7	
			7.0	6.5	6.2	5.9	5.6	6.1	5.8	5.5	5.3	5.2	5.0	4.8	4.6	4.5	4.3	4.1	3.0	
			10.0	6.7	6.4	6.2	6.0	6.2	6.0	5.8	5.6	5.4	5.2	5.1	4.9	4.6	4.5	4.4	3.2	

