

屋内照明器具特性

品番 (品名)	NNN12400																
光源	LDA8L-D-G-E17/S/Z6 ×1 760.0 l m																
管理番号	K0173135(0)DR1																
BZ分類	BZ10																

器具効率	69 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	39 %	室指数	照明率 (X0.01) ZCM																		
下方光束	30 %																				
保守率	良 中 否 0.63 0.6 0.56	0.6	2.9	2.0	1.5	1.1	2.6	1.8	1.3	1.0	2.1	1.5	1.1	8	1.6	1.1	8	5	1		
		0.8	3.5	2.6	2.0	1.6	3.1	2.3	1.8	1.4	2.5	1.9	1.4	1.1	1.9	1.4	1.1	8	3		
		1.0	3.9	3.0	2.4	1.9	3.5	2.7	2.2	1.8	2.7	2.2	1.7	1.4	2.1	1.6	1.3	10	4		
		1.25	4.2	3.4	2.8	2.4	3.8	3.1	2.6	2.1	3.0	2.5	2.0	1.7	2.3	1.9	1.5	13	6		
下方投影面積	cm ²	1.5	4.5	3.8	3.2	2.7	4.1	3.4	2.9	2.5	3.2	2.7	2.3	2.0	2.5	2.1	1.8	1.5	7		
		2.0	4.9	4.2	3.7	3.2	4.4	3.8	3.4	3.0	3.6	3.1	2.7	2.4	2.7	2.4	2.1	1.8	10		
器具間隔最大限	横方向 (A)		縦方向 (B)																		
	H m	0.00 H m	0.00 H m																		
4.0	5.6	5.2	4.8	4.4	5.1	4.7	4.4	4.0	4.2	3.8	3.6	3.3	3.3	3.0	2.8	2.6	1.5				
5.0	5.8	5.4	5.0	4.7	5.3	4.9	4.6	4.3	4.3	4.0	3.8	3.6	3.4	3.2	3.0	2.8	1.7				
7.0	6.0	5.7	5.4	5.1	5.5	5.2	4.9	4.7	4.5	4.3	4.1	3.9	3.6	3.4	3.3	3.1	1.9				
10.0	6.1	5.9	5.7	5.5	5.6	5.4	5.2	5.0	4.7	4.5	4.3	4.2	3.7	3.6	3.5	3.4	2.2				

