

屋内照明器具特性	
品番 (品名)	NNN12620
光源	LDT6L-G/S/T6 ×1 810.0 lm
管理番号	K0163080(0)DB1
BZ分類	BZ10/0.7/BZ9

器具効率	58%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	25%	床	10%				10%				10%				10%				0%	
下方光束	33%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	2.5	1.8	1.3	0.9	2.3	1.6	1.2	0.9	1.9	1.4	1.0	0.7	1.5	1.1	0.8	0.6	0.3
	中	0.6	0.8	3.0	2.3	1.7	1.4	2.8	2.1	1.6	1.3	2.3	1.7	1.4	1.1	1.9	1.4	1.1	0.9	0.5
	否	0.56	1.0	3.4	2.6	2.1	1.7	3.1	2.4	1.9	1.6	2.6	2.0	1.6	1.3	2.1	1.7	1.3	1.1	0.7
			1.25	3.7	3.0	2.5	2.1	3.4	2.8	2.3	1.9	2.8	2.3	1.9	1.6	2.3	1.9	1.6	1.4	0.9
下方投影面積	cm ²	1.5	3.9	3.3	2.8	2.4	3.6	3.0	2.6	2.2	3.0	2.6	2.2	1.9	2.5	2.1	1.8	1.6	1.0	
等価発光面積		2.0	4.3	3.7	3.2	2.8	3.9	3.4	3.0	2.6	3.3	2.9	2.6	2.3	2.7	2.4	2.1	1.9	1.3	
取付高さ		器具間隔最大限	2.5	4.5	4.0	3.6	3.2	4.1	3.7	3.3	3.0	3.5	3.1	2.8	2.6	2.9	2.6	2.4	2.1	1.5
Hm		横方向 (A)	縦方向 (B)	3.0	4.7	4.2	3.8	3.5	4.3	3.9	3.5	3.2	3.6	3.3	3.0	2.8	3.0	2.8	2.5	2.3
Hm	1.54Hm	2.55Hm	4.0	4.9	4.5	4.1	3.8	4.5	4.2	3.9	3.6	3.8	3.6	3.3	3.1	3.2	3.0	2.8	2.6	1.9
			5.0	5.0	4.7	4.4	4.1	4.7	4.4	4.1	3.8	4.0	3.7	3.5	3.3	3.3	3.2	3.0	2.8	2.1
			7.0	5.2	4.9	4.7	4.5	4.8	4.6	4.4	4.2	4.2	4.0	3.8	3.6	3.5	3.4	3.2	3.1	2.3
			10.0	5.3	5.1	4.9	4.8	5.0	4.8	4.6	4.5	4.3	4.1	4.0	3.9	3.7	3.5	3.4	3.3	2.5

