

屋内照明器具特性

品番 (品名)	NTS32241S+NTS92200	
光源	LED4000_85_1670 x1	1670.0 lm
管理番号	K0161316(0)DB1	
BZ分類	BZ4	

器具効率	100%	天井	80%				70%				50%				30%				0%		
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
上方光束	1%	床	10%				10%				10%				10%				0%		
下方光束	99%	室指数	照明率 (X0.01)																ZCM		
保守率	良 中 否	0.81	0.6	5.9	4.8	4.0	3.5	5.8	4.7	4.0	3.5	5.6	4.6	4.0	3.5	5.4	4.5	3.9	3.5	3.3	
		0.77	0.8	7.0	5.9	5.2	4.7	6.9	5.9	5.2	4.7	6.6	5.7	5.1	4.6	6.4	5.6	5.0	4.6	4.4	
		0.68	1.0	7.7	6.7	6.0	5.5	7.5	6.6	6.0	5.5	7.2	6.5	5.9	5.4	7.0	6.3	5.8	5.4	5.2	
			1.25	8.3	7.4	6.7	6.2	8.1	7.3	6.7	6.2	7.8	7.1	6.6	6.2	7.5	7.0	6.5	6.1	5.9	
下方投影面積		cm ²		1.5	8.6	7.9	7.3	6.8	8.5	7.8	7.2	6.7	8.2	7.6	7.1	6.7	7.9	7.4	7.0	6.6	6.4
等価発光面積		cm ²		2.0	9.2	8.5	8.0	7.6	9.0	8.4	7.9	7.5	8.7	8.2	7.8	7.4	8.4	8.0	7.6	7.3	7.1
取付高さ	器具間隔最大限		2.5	9.5	8.9	8.5	8.1	9.3	8.8	8.4	8.0	9.0	8.6	8.2	7.9	8.8	8.4	8.1	7.8	7.6	
	横方向 (A)	縦方向 (B)	3.0	9.7	9.2	8.8	8.4	9.5	9.1	8.7	8.4	9.3	8.9	8.6	8.3	9.0	8.7	8.4	8.1	7.9	
Hm	0.89Hm	1.20Hm	4.0	10.0	9.6	9.2	8.9	9.8	9.5	9.2	8.9	9.5	9.2	9.0	8.7	9.3	9.0	8.8	8.6	8.3	
			5.0	10.1	9.8	9.5	9.3	10.0	9.7	9.4	9.2	9.7	9.5	9.2	9.0	9.4	9.2	9.1	8.9	8.6	
			7.0	10.3	10.1	9.9	9.7	10.2	10.0	9.8	9.6	9.9	9.7	9.6	9.4	9.7	9.5	9.4	9.2	8.9	
			10.0	10.5	10.3	10.1	10.0	10.3	10.2	10.0	9.9	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2	

