

屋内照明器具特性	
品番 (品名)	NNN12622
光源	LDT8L-G/Z60/S/W ×1 810.0 lm
管理番号	K0138593(0)DB1
BZ分類	BZ3

器具効率	23%	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
上方光束	13%	床	10%				10%				10%				10%				0%
下方光束	10%		10%				10%				10%				10%				0%
器具効率		室指数	照明率 (X0.01)																ZCM
保守率	良 0.63	0.6	12	9	8	7	11	9	7	6	9	7	6	6	7	6	5	5	4
	中 0.6	0.8	13	11	10	9	12	11	9	8	10	9	8	7	9	8	7	6	5
	否 0.56	1.0	15	13	11	10	14	12	11	10	12	10	9	8	10	9	8	7	5
		1.25	16	14	13	12	15	13	12	11	12	11	10	10	10	9	9	8	6
下方投影面積	cm ²	1.5	17	15	14	13	16	14	13	12	13	12	11	10	11	10	9	7	
等価発光面積	cm ²	2.0	18	17	15	14	17	15	14	14	14	13	12	12	12	11	10	7	
取付高さ	器具間隔最大限		2.5	19	17	16	16	17	16	15	15	14	14	13	13	12	11	11	8
	横方向 (A)	縦方向 (B)	3.0	19	18	17	16	18	17	16	15	15	14	14	13	12	12	11	8
H _m	1.03H _m	1.20H _m	4.0	20	19	18	17	18	17	17	16	15	15	14	14	13	12	12	9
			5.0	20	19	19	18	19	18	17	17	16	15	15	15	13	13	12	9
			7.0	20	20	19	19	19	18	18	18	16	16	15	15	13	13	13	9
			10.0	21	20	20	20	19	19	19	18	16	16	16	16	13	13	13	9

