

屋内照明器具特性

品番 (品名)	NTS32243S+NTS92200	
光源	LED3000_85_1605 ×1	1605.0 lm
管理番号	K0161316(0)DB1	
BZ分類	BZ4	

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	1%	床	10%				10%				10%				10%				0%	
下方光束	99%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否	0.81	0.6	5.9	4.8	4.0	3.5	5.8	4.7	4.0	3.5	5.6	4.6	4.0	3.5	5.4	4.5	3.9	3.5	3.3
		0.77	0.8	7.0	5.9	5.2	4.7	6.9	5.9	5.2	4.7	6.6	5.7	5.1	4.6	6.4	5.6	5.0	4.6	4.4
		0.68	1.0	7.7	6.7	6.0	5.5	7.5	6.6	6.0	5.5	7.2	6.5	5.9	5.4	7.0	6.3	5.8	5.4	5.2
			1.25	8.3	7.4	6.7	6.2	8.1	7.3	6.7	6.2	7.8	7.1	6.6	6.2	7.5	7.0	6.5	6.1	5.9
下方投影面積	c m ²	1.5	8.6	7.9	7.3	6.8	8.5	7.8	7.2	6.7	8.2	7.6	7.1	6.7	7.9	7.4	7.0	6.6	6.4	
		2.0	9.2	8.5	8.0	7.6	9.0	8.4	7.9	7.5	8.7	8.2	7.8	7.4	8.4	8.0	7.6	7.3	7.1	
取付高さ	器具間隔最大限		2.5	9.5	8.9	8.5	8.1	9.3	8.8	8.4	8.0	9.0	8.6	8.2	7.9	8.8	8.4	8.1	7.8	7.6
	横方向 (A)	縦方向 (B)	3.0	9.7	9.2	8.8	8.4	9.5	9.1	8.7	8.4	9.3	8.9	8.6	8.3	9.0	8.7	8.4	8.1	7.9
H m	0.89 H m	1.20 H m	4.0	10.0	9.6	9.2	8.9	9.8	9.5	9.2	8.9	9.5	9.2	9.0	8.7	9.3	9.0	8.8	8.6	8.3
			5.0	10.1	9.8	9.5	9.3	10.0	9.7	9.4	9.2	9.7	9.5	9.2	9.0	9.4	9.2	9.1	8.9	8.6
			7.0	10.3	10.1	9.9	9.7	10.2	10.0	9.8	9.6	9.9	9.7	9.6	9.4	9.7	9.5	9.4	9.2	8.9
			10.0	10.5	10.3	10.1	10.0	10.3	10.2	10.0	9.9	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2

