

屋内照明器具特性

品番 (品名)	NNN90623																	
光源	NNN90623-65RA66 x1 155.0lm																	
管理番号	K0128332(0)DR1																	
BZ分類	BZ10/2.3/BZ9/3.5/BZ8/4.5/BZ7/8.5/BZ6																	

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	100%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01) ZCM																	
保守率	良	0.69	0.6	4.2	2.6	1.6	9	4.0	2.5	1.6	9	3.7	2.4	1.5	9	3.4	2.3	1.5	9	6
	中	0.67	0.8	5.0	3.4	2.3	15	4.8	3.3	2.2	15	4.4	3.1	2.2	14	4.1	2.9	2.1	14	11
	否	0.63	1.0	5.6	4.0	2.8	19	5.3	3.8	2.8	19	4.9	3.6	2.7	19	4.6	3.4	2.6	19	16
			1.25	6.2	4.6	3.5	26	5.9	4.5	3.4	25	5.5	4.2	3.3	25	5.1	4.0	3.2	25	21
下方投影面積	c m ²		1.5	6.7	5.2	4.1	31	6.4	5.1	4.0	31	6.0	4.8	3.8	31	5.6	4.5	3.7	30	27
等価発光面積	c m ²		2.0	7.5	6.2	5.1	42	7.2	6.0	5.0	42	6.8	5.7	4.9	41	6.3	5.5	4.7	41	37
取付高さ	器具間隔最大限		2.5	8.0	6.9	5.9	51	7.8	6.7	5.9	51	7.4	6.5	5.7	50	6.9	6.2	5.5	49	46
	横方向 (A)	縦方向 (B)	3.0	8.5	7.5	6.6	59	8.2	7.3	6.5	58	7.8	7.0	6.4	57	7.4	6.8	6.2	57	53
H _m	2.98H _m	2.98H _m	4.0	9.0	8.2	7.5	69	8.8	8.1	7.4	69	8.4	7.8	7.2	67	8.1	7.5	7.1	66	63
			5.0	9.4	8.7	8.1	76	9.2	8.6	8.0	75	8.8	8.3	7.8	74	8.5	8.0	7.6	73	69
			7.0	9.8	9.3	8.8	84	9.6	9.1	8.7	83	9.3	8.9	8.5	82	9.0	8.6	8.3	80	77
			10.0	10.1	9.7	9.4	91	9.9	9.6	9.3	90	9.6	9.3	9.1	88	9.3	9.1	8.9	87	83

