

|          |  |
|----------|--|
| 屋内照明器具特性 |  |
| 品番 (品名)  | NNNS 1 2 6 2 3 B                       |
| 光源       | LDT8L-G / Z60 / S / W ×1      810.0 lm |
| 管理番号     | K0138598 ( 0 ) DB 1                    |
| BZ分類     | BZ10                                   |

|        |                 |         |               |      |     |     |      |      |     |     |      |      |     |     |      |      |     |     |     |     |
|--------|-----------------|---------|---------------|------|-----|-----|------|------|-----|-----|------|------|-----|-----|------|------|-----|-----|-----|-----|
| 器具効率   | 60 %            | 反射率     | 天井            | 80 % |     |     |      | 70 % |     |     |      | 50 % |     |     |      | 30 % |     |     |     | 0 % |
|        |                 |         | 壁             | 70   | 50  | 30  | 10   | 70   | 50  | 30  | 10   | 70   | 50  | 30  | 10   | 70   | 50  | 30  | 10  | 0 % |
| 上方光束   | 29 %            | 床       | 10 %          |      |     |     | 10 % |      |     |     | 10 % |      |     |     | 10 % |      |     |     | 0 % |     |
| 下方光束   | 31 %            | 室指数     | 照明率 ( X0.01 ) |      |     |     |      |      |     |     |      |      |     |     |      |      |     |     | ZCM |     |
| 保守率    | 良               | 0.63    | 0.6           | 2.5  | 1.7 | 1.2 | 9    | 2.3  | 1.6 | 1.1 | 8    | 1.8  | 1.3 | 9   | 6    | 1.4  | 1.0 | 7   | 5   | 2   |
|        | 中               | 0.6     | 0.8           | 3.0  | 2.2 | 1.7 | 1.3  | 2.7  | 2.0 | 1.5 | 1.2  | 2.2  | 1.6 | 1.2 | 9    | 1.7  | 1.3 | 1.0 | 7   | 3   |
|        | 否               | 0.56    | 1.0           | 3.3  | 2.6 | 2.0 | 1.6  | 3.0  | 2.4 | 1.9 | 1.5  | 2.5  | 1.9 | 1.5 | 1.2  | 1.9  | 1.5 | 1.2 | 9   | 5   |
|        |                 |         | 1.25          | 3.7  | 2.9 | 2.4 | 2.0  | 3.3  | 2.7 | 2.2 | 1.8  | 2.7  | 2.2 | 1.8 | 1.5  | 2.1  | 1.8 | 1.4 | 1.2 | 6   |
| 下方投影面積 | cm <sup>2</sup> | 1.5     | 3.9           | 3.2  | 2.7 | 2.3 | 3.6  | 3.0  | 2.5 | 2.1 | 2.9  | 2.4  | 2.1 | 1.7 | 2.3  | 1.9  | 1.6 | 1.4 | 8   |     |
| 等価発光面積 |                 | 2.0     | 4.3           | 3.7  | 3.2 | 2.8 | 3.9  | 3.4  | 2.9 | 2.6 | 3.2  | 2.8  | 2.4 | 2.1 | 2.6  | 2.2  | 2.0 | 1.7 | 1.0 |     |
| 取付高さ   | 器具間隔最大限         |         | 2.5           | 4.5  | 4.0 | 3.5 | 3.1  | 4.1  | 3.7 | 3.2 | 2.9  | 3.4  | 3.0 | 2.7 | 2.4  | 2.8  | 2.5 | 2.2 | 2.0 | 1.2 |
|        | 横方向 (A)         | 縦方向 (B) | 3.0           | 4.7  | 4.2 | 3.8 | 3.4  | 4.3  | 3.9 | 3.5 | 3.2  | 3.6  | 3.2 | 2.9 | 2.7  | 2.9  | 2.6 | 2.4 | 2.2 | 1.4 |
| Hm     | 0.00Hm          | 0.00Hm  | 4.0           | 4.9  | 4.5 | 4.1 | 3.8  | 4.5  | 4.2 | 3.8 | 3.5  | 3.8  | 3.5 | 3.2 | 3.0  | 3.1  | 2.9 | 2.7 | 2.5 | 1.6 |
|        |                 |         | 5.0           | 5.1  | 4.7 | 4.4 | 4.1  | 4.7  | 4.3 | 4.1 | 3.8  | 3.9  | 3.7 | 3.4 | 3.2  | 3.2  | 3.0 | 2.8 | 2.7 | 1.8 |
|        |                 |         | 7.0           | 5.2  | 5.0 | 4.7 | 4.5  | 4.8  | 4.6 | 4.4 | 4.1  | 4.1  | 3.9 | 3.7 | 3.5  | 3.4  | 3.2 | 3.1 | 2.9 | 2.0 |
|        |                 |         | 10.0          | 5.4  | 5.2 | 5.0 | 4.8  | 5.0  | 4.8 | 4.6 | 4.4  | 4.2  | 4.1 | 3.9 | 3.8  | 3.5  | 3.4 | 3.3 | 3.2 | 2.3 |

