

屋内照明器具特性

品番 (品名)	NNNS 1 2 6 2 3 W	
光源	LDT6L - G / S / T6 ×1	810.0 lm
管理番号	K0163082 (0) DB 1	
BZ分類	BZ10	

器具効率	69 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		34 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	35 %	床	10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
下方投影面積	cm ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	40.0	50.0
	等価発光面積		cm ²	1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	40.0
取付高さ	器具間隔最大限		2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0
	横方向 (A)	縦方向 (B)	2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0
H _m	0.00H _m	0.00H _m	2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0
			3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0	10.0
			4.0	5.0	6.0	7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0	10.0	12.5
			5.0	6.0	7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0	10.0	12.5	15.0
			6.0	7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0	10.0	12.5	15.0	20.0
			7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0	10.0	12.5	15.0	20.0	25.0
			10.0	12.5	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0	10.0	12.5	15.0	20.0	25.0	30.0	40.0

