

屋内照明器具特性	
品番 (品名)	NNNS 1 2 6 2 3 W
光源	LDT8L-G / Z60 / S / W ×1 810.0 lm
管理番号	K0138598 (0) DB 1
BZ分類	BZ10

器具効率	60 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	29 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	31 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	2.5	1.7	1.2	9	2.3	1.6	1.1	8	1.8	1.3	9	6	1.4	1.0	7	5	2
	中	0.6	0.8	3.0	2.2	1.7	1.3	2.7	2.0	1.5	1.2	2.2	1.6	1.2	9	1.7	1.3	1.0	7	3
	否	0.56	1.0	3.3	2.6	2.0	1.6	3.0	2.4	1.9	1.5	2.5	1.9	1.5	1.2	1.9	1.5	1.2	9	5
			1.25	3.7	2.9	2.4	2.0	3.3	2.7	2.2	1.8	2.7	2.2	1.8	1.5	2.1	1.8	1.4	1.2	6
下方投影面積	cm ²	1.5	3.9	3.2	2.7	2.3	3.6	3.0	2.5	2.1	2.9	2.4	2.1	1.7	2.3	1.9	1.6	1.4	8	
等価発光面積		2.0	4.3	3.7	3.2	2.8	3.9	3.4	2.9	2.6	3.2	2.8	2.4	2.1	2.6	2.2	2.0	1.7	1.0	
取付高さ	器具間隔最大限		2.5	4.5	4.0	3.5	3.1	4.1	3.7	3.2	2.9	3.4	3.0	2.7	2.4	2.8	2.5	2.2	2.0	1.2
	横方向 (A)	縦方向 (B)	3.0	4.7	4.2	3.8	3.4	4.3	3.9	3.5	3.2	3.6	3.2	2.9	2.7	2.9	2.6	2.4	2.2	1.4
Hm	0.00Hm	0.00Hm	4.0	4.9	4.5	4.1	3.8	4.5	4.2	3.8	3.5	3.8	3.5	3.2	3.0	3.1	2.9	2.7	1.6	
			5.0	5.1	4.7	4.4	4.1	4.7	4.3	4.1	3.8	3.9	3.7	3.4	3.2	3.2	3.0	2.8	1.8	
			7.0	5.2	5.0	4.7	4.5	4.8	4.6	4.4	4.1	4.1	3.9	3.7	3.5	3.4	3.2	3.1	2.0	
			10.0	5.4	5.2	5.0	4.8	5.0	4.8	4.6	4.4	4.2	4.1	3.9	3.8	3.5	3.4	3.3	2.3	

