

# 屋内照明器具特性

|         |                    |           |
|---------|--------------------|-----------|
| 品番 (品名) | NNN17511K+NNN89990 |           |
| 光源      | LED4000_80_5250 x1 | 5250.0 lm |
| 管理番号    | K0150638(0)DB1     |           |
| BZ分類    | BZ1/1.8/BZ2        |           |

|        |               |         |      |     |     |     |     |     |     |     |     |     |     |    |     |     |    |    |    |     |
|--------|---------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|-----|----|----|----|-----|
| 器具効率   | 100%          | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |    | 30% |     |    |    | 0% |     |
|        | 上方光束<br>3%    |         | 反射率  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10  | 70  | 50 | 30 | 10 | 0%  |
| 下方光束   | 97%           | 床       |      | 10% |     |     |     | 10% |     |     |     | 10% |     |    |     | 10% |    |    |    | 0%  |
| 室指数    | 照明率 ( X0.01 ) |         |      |     |     |     |     |     |     |     |     |     |     |    |     |     |    |    |    | ZCM |
| 保守率    | 良             | 0.76    | 0.6  | 74  | 65  | 60  | 57  | 73  | 65  | 60  | 56  | 71  | 64  | 59 | 56  | 69  | 63 | 59 | 56 | 54  |
|        | 中             | 0.72    | 0.8  | 81  | 74  | 68  | 65  | 80  | 73  | 68  | 65  | 78  | 72  | 67 | 64  | 76  | 70 | 67 | 64 | 62  |
|        | 否             | 0.64    | 1.0  | 86  | 79  | 74  | 70  | 85  | 78  | 74  | 70  | 82  | 77  | 73 | 70  | 80  | 75 | 72 | 69 | 67  |
|        | 下方投影面積        |         | 1.25 | 90  | 84  | 79  | 76  | 88  | 83  | 79  | 75  | 86  | 81  | 77 | 74  | 84  | 80 | 76 | 74 | 72  |
| 等価発光面積 |               |         | 1.5  | 93  | 87  | 83  | 79  | 91  | 86  | 82  | 79  | 88  | 84  | 81 | 78  | 86  | 82 | 79 | 77 | 75  |
|        |               |         | 2.0  | 96  | 91  | 88  | 85  | 95  | 90  | 87  | 84  | 92  | 88  | 85 | 83  | 89  | 86 | 84 | 82 | 79  |
| 取付高さ   | 器具間隔最大限       |         | 2.5  | 98  | 94  | 91  | 88  | 97  | 93  | 90  | 87  | 94  | 91  | 88 | 86  | 91  | 89 | 87 | 85 | 82  |
|        | 横方向 (A)       | 縦方向 (B) | 3.0  | 100 | 96  | 93  | 91  | 98  | 95  | 92  | 90  | 95  | 93  | 90 | 88  | 93  | 91 | 89 | 87 | 84  |
| Hm     | 0.95Hm        | 0.94Hm  | 4.0  | 102 | 99  | 96  | 94  | 100 | 98  | 95  | 93  | 97  | 95  | 93 | 92  | 95  | 93 | 91 | 90 | 87  |
|        |               |         | 5.0  | 103 | 100 | 98  | 97  | 101 | 99  | 97  | 96  | 98  | 97  | 95 | 94  | 96  | 94 | 93 | 92 | 89  |
|        |               |         | 7.0  | 104 | 102 | 101 | 99  | 103 | 101 | 100 | 98  | 100 | 98  | 97 | 96  | 97  | 96 | 95 | 94 | 91  |
|        |               |         | 10.0 | 105 | 104 | 103 | 102 | 104 | 102 | 101 | 100 | 101 | 100 | 99 | 98  | 98  | 97 | 96 | 96 | 92  |

