

# 屋内照明器具特性

|         |                     |             |
|---------|---------------------|-------------|
| 品番 (品名) | NNN17900+NNN89990   |             |
| 光源      | LED5000_80_10420 ×1 | 10420.0 1 m |
| 管理番号    | K0150632(0)DB1      |             |
| BZ分類    | BZ1/2.8/BZ2         |             |

|        |         |                 |              |     |     |     |     |     |     |     |     |     |    |    |     |    |    |    |    |    |  |  |     |
|--------|---------|-----------------|--------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|----|----|----|----|----|--|--|-----|
| 器具効率   | 100%    | 天井              | 80%          |     |     |     | 70% |     |     |     | 50% |     |    |    | 30% |    |    |    | 0% |    |  |  |     |
|        |         | 壁               | 70           | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10 | 70  | 50 | 30 | 10 | 0% |    |  |  |     |
| 上方光束   | 4%      | 床               | 10%          |     |     |     | 10% |     |     |     | 10% |     |    |    | 10% |    |    |    | 0% |    |  |  |     |
| 下方光束   | 96%     | 室指数             | 照明率 ( X0.01) |     |     |     |     |     |     |     |     |     |    |    |     |    |    |    |    |    |  |  | ZCM |
| 保守率    | 良       | 0.76            | 0.6          | 74  | 66  | 61  | 58  | 73  | 66  | 61  | 57  | 71  | 65 | 60 | 57  | 69 | 63 | 60 | 57 | 55 |  |  |     |
|        | 中       | 0.72            | 0.8          | 81  | 74  | 69  | 65  | 80  | 73  | 69  | 65  | 78  | 72 | 68 | 65  | 76 | 71 | 67 | 64 | 62 |  |  |     |
|        | 否       | 0.64            | 1.0          | 86  | 79  | 75  | 71  | 85  | 79  | 74  | 71  | 82  | 77 | 73 | 70  | 80 | 75 | 72 | 69 | 67 |  |  |     |
|        |         |                 | 1.25         | 90  | 84  | 80  | 76  | 89  | 83  | 79  | 76  | 86  | 81 | 78 | 75  | 83 | 79 | 76 | 74 | 72 |  |  |     |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5          | 93  | 87  | 83  | 80  | 91  | 86  | 82  | 79  | 88  | 84 | 81 | 78  | 86 | 82 | 79 | 77 | 75 |  |  |     |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0          | 96  | 92  | 88  | 85  | 95  | 90  | 87  | 84  | 92  | 88 | 85 | 83  | 89 | 86 | 84 | 81 | 79 |  |  |     |
| 取付高さ   | 器具間隔最大限 |                 | 2.5          | 98  | 94  | 91  | 88  | 97  | 93  | 90  | 88  | 94  | 91 | 88 | 86  | 91 | 88 | 86 | 84 | 82 |  |  |     |
|        | 横方向 (A) | 縦方向 (B)         | 3.0          | 100 | 96  | 93  | 91  | 98  | 95  | 92  | 90  | 95  | 92 | 90 | 88  | 92 | 90 | 88 | 87 | 83 |  |  |     |
| Hm     | 0.97Hm  | 0.97Hm          | 4.0          | 101 | 99  | 96  | 94  | 100 | 97  | 95  | 93  | 97  | 95 | 93 | 91  | 94 | 92 | 91 | 89 | 86 |  |  |     |
|        |         |                 | 5.0          | 103 | 100 | 98  | 97  | 101 | 99  | 97  | 95  | 98  | 96 | 95 | 93  | 95 | 94 | 92 | 91 | 88 |  |  |     |
|        |         |                 | 7.0          | 104 | 102 | 101 | 99  | 102 | 101 | 99  | 98  | 99  | 98 | 97 | 96  | 96 | 95 | 94 | 93 | 90 |  |  |     |
|        |         |                 | 10.0         | 105 | 104 | 102 | 101 | 103 | 102 | 101 | 100 | 100 | 99 | 98 | 97  | 97 | 96 | 96 | 95 | 91 |  |  |     |

