

屋内照明器具特性

品番 (品名)	NNLK42742 + NNL4600EX														
光源	LED5000_85_6710 x1 6710.0 lm														
管理番号	K0129806 (2) DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	2%	反射率	床	10%				10%				10%				10%				0%
下方光束	98%		室指数	照明率 (X0.01) ZCM																
保守率	良 0.83 中 0.81 否 0.77	0.6	55	42	34	29	53	42	34	29	51	40	33	28	48	39	33	28	26	
		0.8	65	53	44	39	63	52	44	38	60	50	43	38	57	49	42	38	35	
		1.0	71	60	52	46	69	59	51	46	66	57	50	45	63	55	49	45	42	
		1.25	77	67	59	53	75	66	58	53	72	64	57	52	69	62	56	51	49	
下方投影面積	c m ²	1.5	81	72	65	59	79	71	64	58	76	68	62	57	73	66	61	57	54	
		2.0	87	79	72	67	85	78	72	66	82	75	70	65	78	73	68	64	62	
取付高さ	器具間隔最大限		2.5	91	84	78	73	89	82	77	72	85	80	75	71	82	77	73	70	67
	横方向 (A)	縦方向 (B)	3.0	93	87	82	77	91	86	81	76	88	83	79	75	85	81	77	74	71
1.5m	2.02m	2.2m	4.0	97	92	87	83	95	90	86	82	91	88	84	81	88	85	82	79	76
2	2.67	2.79	5.0	99	94	91	87	97	93	90	86	94	90	87	85	91	88	85	83	80
2.5	3.32	3.39	7.0	101	98	95	92	99	96	94	91	96	94	91	89	93	91	89	87	84
3	3.97	4.01	10.0	103	101	98	96	101	99	97	95	98	96	95	93	95	94	92	91	88

