

屋内照明器具特性	
品番 (品名)	L G C 6 1 1 2 2
光源	LED6200_70_5800 ×1 5800.0 lm
管理番号	K0168479 (0) DB 1
B Z 分類	B Z 5

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
				室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 6 3	0 . 6	5 5	4 2	3 4	2 9	5 3	4 2	3 4	2 9	5 1	4 0	3 3	2 8	4 8	3 9	3 3	2 8	2 6				
			0 . 6	0 . 8	6 5	5 3	4 5	3 9	6 3	5 2	4 5	3 9	6 0	5 1	4 4	3 9	5 8	4 9	4 3	3 8	3 6				
			0 . 5 6	1 . 0	7 2	6 1	5 3	4 7	7 0	6 0	5 2	4 6	6 7	5 8	5 1	4 6	6 4	5 6	5 0	4 5	4 3				
				1 . 2 5	7 8	6 8	6 0	5 4	7 6	6 7	6 0	5 4	7 3	6 5	5 8	5 3	7 0	6 3	5 7	5 3	5 0				
下方投影面積 等価発光面積		c m ²		1 . 5	8 2	7 3	6 6	6 0	8 0	7 2	6 5	6 0	7 7	7 0	6 4	5 9	7 4	6 7	6 2	5 8	5 5				
				2 . 0	8 8	8 0	7 4	6 9	8 6	7 9	7 3	6 8	8 3	7 7	7 2	6 7	7 9	7 4	7 0	6 6	6 3				
				2 . 5	9 2	8 5	7 9	7 5	9 0	8 4	7 8	7 4	8 6	8 1	7 7	7 3	8 3	7 9	7 5	7 2	6 9				
取付 高さ	器具間隔最大限			3 . 0	9 4	8 8	8 3	7 9	9 2	8 7	8 2	7 8	8 9	8 5	8 1	7 7	8 6	8 2	7 9	7 6	7 3				
	横方向 (A)	縦方向 (B)		4 . 0	9 7	9 3	8 9	8 5	9 6	9 1	8 8	8 4	9 2	8 9	8 6	8 3	8 9	8 6	8 4	8 1	7 8				
H m	1 . 3 7 H m	1 . 3 7 H m		5 . 0	9 9	9 6	9 2	8 9	9 8	9 4	9 1	8 8	9 5	9 2	8 9	8 6	9 2	8 9	8 7	8 5	8 1				
				7 . 0	1 0 2	9 9	9 6	9 4	1 0 0	9 7	9 5	9 3	9 7	9 5	9 3	9 1	9 4	9 2	9 1	8 9	8 6				
				1 0 . 0	1 0 3	1 0 1	9 9	9 8	1 0 2	1 0 0	9 8	9 6	9 9	9 7	9 6	9 4	9 6	9 5	9 4	9 2	8 9				

