

# 屋内照明器具特性

品番(品名)	NTS32713S+NTS92151	
光源	LED3000_70_670 x1	670.0 lm
管理番号	K0156488(1)DJ1	
BZ分類	BZ1	

器具効率	102%	天井	80%				70%				50%				30%				0%		
	上方光束 0%		下方光束 102%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良 0.67	中 0.63	否 0.56	0.6	1.02	1.00	0.98	0.97	1.02	1.00	0.98	0.97	1.01	0.99	0.98	0.97	1.01	0.99	0.98	0.97	0.96
	1.0			1.05	1.03	1.02	1.00	1.05	1.03	1.01	1.00	1.03	1.02	1.01	1.00	1.03	1.01	1.00	0.99	0.98	0.98
	1.25			1.06	1.04	1.03	1.02	1.05	1.04	1.02	1.01	1.04	1.03	1.02	1.01	1.03	1.02	1.01	1.00	0.99	0.99
下方投影面積 等価発光面積	cm <sup>2</sup>																				
	cm <sup>2</sup>																				
取付高さ	器具間隔最大限																				
	Hm	0.25Hm	0.25Hm																		
Hm			4.0	1.09	1.08	1.07	1.06	1.06	1.08	1.07	1.06	1.05	1.06	1.05	1.04	1.04	1.04	1.03	1.03	1.01	
			5.0	1.09	1.09	1.08	1.07	1.08	1.08	1.07	1.07	1.06	1.06	1.05	1.05	1.05	1.04	1.04	1.03	1.01	
			7.0	1.10	1.09	1.09	1.08	1.09	1.08	1.08	1.07	1.07	1.06	1.06	1.05	1.05	1.04	1.04	1.03	1.01	
			10.0	1.10	1.10	1.09	1.09	1.09	1.09	1.08	1.08	1.07	1.07	1.06	1.06	1.05	1.05	1.04	1.03	1.01	

