

屋内照明器具特性	
品番 (品名)	NNN12260
光源	LDA5L-D-G-E17/S/Z4 ×1 440.0 mm
管理番号	K0172972(0)DR1
BZ分類	BZ8/0.7/BZ7

器具効率	84%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	54%	床	10%				10%				10%				10%				0%	
下方光束	30%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	3.8	2.8	2.2	1.8	3.4	2.5	2.0	1.6	2.7	2.0	1.6	1.3	2.0	1.6	1.2	1.0	0.5
	中	0.6	0.8	4.5	3.5	2.9	2.4	4.0	3.2	2.6	2.2	3.2	2.6	2.1	1.8	2.4	2.0	1.6	1.4	0.7
	否	0.56	1.0	5.0	4.1	3.4	2.9	4.5	3.7	3.1	2.7	3.5	2.9	2.5	2.2	2.7	2.3	1.9	1.7	0.9
			1.25	5.4	4.6	3.9	3.5	4.9	4.2	3.6	3.2	3.9	3.3	2.9	2.6	2.9	2.5	2.2	2.0	1.1
下方投影面積		cm ²	1.5	5.8	5.0	4.4	3.9	5.2	4.5	4.0	3.5	4.1	3.6	3.2	2.9	3.1	2.8	2.5	2.2	1.2
等価発光面積		cm ²	2.0	6.2	5.5	5.0	4.5	5.6	5.0	4.5	4.1	4.5	4.0	3.7	3.4	3.4	3.1	2.8	2.6	1.5
取付高さ	器具間隔最大限		2.5	6.5	5.9	5.4	5.0	5.9	5.4	4.9	4.6	4.7	4.3	4.0	3.7	3.6	3.3	3.1	2.9	1.6
	横方向 (A)	縦方向 (B)	3.0	6.7	6.2	5.7	5.3	6.1	5.6	5.2	4.9	4.9	4.5	4.2	4.0	3.7	3.5	3.3	3.1	1.8
1.5m	2.53m	2.06m	4.0	7.0	6.5	6.2	5.8	6.3	5.9	5.6	5.3	5.1	4.8	4.6	4.3	3.9	3.7	3.5	3.4	2.0
2	3.37	2.74	5.0	7.1	6.8	6.4	6.1	6.5	6.2	5.9	5.6	5.2	5.0	4.8	4.6	4.0	3.9	3.7	3.6	2.1
2.5	4.22	3.43	7.0	7.3	7.1	6.8	6.6	6.7	6.4	6.2	6.0	5.4	5.2	5.1	4.9	4.2	4.1	3.9	3.8	2.3
3	5.06	4.12	10.0	7.5	7.3	7.1	6.9	6.8	6.6	6.5	6.3	5.6	5.4	5.3	5.2	4.3	4.2	4.1	4.0	2.4

